



| POLE | MATERIAL NUMBER | ENGINEERING NUMBER |
|------|-----------------|--------------------|
| 3 | 1200905001 | 4R3H400013 |
| 4 | 1200310118 | 4R4H400013 |

| CONNECTOR SPECIFICATION: | |
|--------------------------|----------------------|
| VOLTAGE RATING | 3-4POL:60V/AC 75V/DC |
| AMPERAGE RATING | 3 AMPS |
| PROTECTION | IP67 |
| OPERATING TEMPERATURE | -25°C TO +90°C |

| ITEM | COMPONENT | MATERIAL | FINISH |
|------|----------------|--------------------|------------------|
| 1 | INSERT | POLYURETHANE (PUR) | BLACK |
| 2 | CONTACT SOCKET | COPPER ALLOY | GOLD OVER NICKEL |
| 3 | SHELL | BRASS | NICKEL PLATED |
| 4 | LOCKNUT | BRASS | NICKEL PLATED |
| 5 | O-RING | FPM | RED |
| 6 | O-RING | VITON | BLACK |

| | | | | | | |
|--|--|--|---|---|--|--|
| DESCRIPTION EC NO.: WEU2010-0338 DRWN: REISSNER 2010/02/15 CH'KD: RE APPR: FPACHER 2010/02/24 REV 1 | QUALITY SYMBOLS ▽ = 0 ▽ = 0 | GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± 0.1 ± --- ANGULAR ± --- ° | DIMENSION STYLE MM DRAWN BY DATE REISSNER 2010/02/15 CHECKED BY DATE FP 2010/02/15 APPROVED BY DATE FPACHER 2010/02/19 | SCALE 2:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION | NC-XP-FE/FE REC-PG7 PCB MOUNT ---- MOLEX INCORPORATED DOCUMENT NO. SD-120090-012 SHEET NO. 1 OF 1 | |
| | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | SEE TABLE | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | |
| | SIZE A3 | | | | | |
| | | | | | | |