





APPROVED: _____
 DATE: _____ TITLE: _____



Rev	AWO #	Description	Date	Appr
-		RELEASED	9/16/04	
A		REVISED SPEC.	5/17/11	

RECOMMENDED PCB LAYOUT



A = .165 [4.20] x No. of Spaces + .205 [5.20]
 B = .165 [4.20] x No. of Spaces
 C = .165 [4.20] x No. of Spaces + .370 [9.40]

SPECIFICATIONS:
 Material: Nylon 66, rated UL 94V-2
 Insulator color: Natural
 Contacts: Brass
 Plating:
 Tin over Copper underplate overall
 Electrical:
 Operating voltage: 250 VAC max
 Current rating: 7 Amps max
 Insulation resistance: 1000 Mohms min
 Dielectric withstanding voltage: 1500 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -25°C to +85°C
 Environmental:
 Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXXX ± .015
.XXX ± .015	ØXXX ± .010

APPROVALS: _____ DATE: _____

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: STRAIGHT HOUSING, MALE TERMINAL
 PCB MOUNT WITH PEGS

DRAWN: SS 9/16/04
 CHECKED: _____
 APPROVED: _____

SIZE: X	PART NO.: DMF-XX-S-P	REV: A
REF: S0001BT	SCALE: NTS	SHEET 1 OF 1



6

5

4

3

2


1

Rev	AWO #	Description	Date	Appr
		SEE SHT 1 OF 2 FOR REVISION		


APPROVED: _____

DATE: _____ TITLE: _____


2 POSITION




8 POSITION




14 POSITION




20 POSITION




4 POSITION




10 POSITION




16 POSITION




22 POSITION




6 POSITION




12 POSITION



18 POSITION



24 POSITION



A

B

C

D

A

B

C

D

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: STRAIGHT HOUSING, MALE TERMINAL
 PCB MOUNT WITH PEGS

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES [MM]		HOLE SIZE	
INCHES	± .10	ØXX	± .10
.XX	± .020	ØXXX	± .015
.XXX	± .015	ØXXXX	± .010
APPROVALS:	DATE		
DRAWN	SS	9/16/04	
CHECKED			
APPROVED			
SIZE	PART NO.	REV.	
X	DMF-XX-S-P	A	
REF:	SCALE: NTS	SHEET 2 OF 2	

6

5

4

3

2

1