



SS Stainless Steel

Specification



GN 6336.4

- Star knob
Plastic
Technopolymer (Polyamide PA) **ST**
Shock-resistant, black, matte finish
- Star knob
Plastic
Duroplast (Phenolic PF) **SK**
Black, shiny finish
(only available in metric sizes)
- Threaded stud
Steel, zinc plated, blue passivated finish

GN 6336.5

- Star knob
Plastic
Technopolymer (Polyamide PA) **ST**
Shock-resistant, black, matte finish
- Threaded stud
Stainless steel
M5 - M10:
European Standard No. 1.4567 (AISI 304 Cu)
M12:
European Standard No. 1.4305 (AISI 303)
- Star knob
Plastic
Duroplast (Phenolic PF) **SK**
Black, shiny finish
- Threaded stud
Stainless steel A2

• RoHS compliant

Information

GN 6336.4 and GN 6336.5 star knobs comply with DIN 6336 type L.

see also...

- Star Knobs GN 6336.10 (with Brass or Nylon Tip)
- Star Knobs GN 6336.12 (with Toggle Thrust Pad)
- Star Knobs GN 6336.13 (with Loss Protection)
- Star Knobs GN 6336.4 / GN 6336.5 with Loss Protection GN 111.7

On request

- Special shorter than listed stud lengths and various stud tips

How to order (Inch, steel threaded stud)	1 Material
GN 6336.4-ST-25-1/4X20-15	2 Handle diameter d_1
	3 Thread d_2
	4 Length l

How to order (Metric, stainless steel threaded stud)	1 Material
GN 6336.5-ST-63-M12-40	2 Handle diameter d_1
	3 Thread d_2
	4 Length l

Inch table

Dimensions in: inches - millimeters

d ₁	d ₂	Length l ≈											d ₃	h ₁	h ₂
		GN 6336.4 ST						GN 6336.5 ST							
0.98 25	1/4 x 20	0.59 15	0.87 22	1.10 28	-	-	-	0.59 15	0.87 22	1.10 28	1.34 34	-	0.47 12	0.63 16	0.31 8
1.26 32	1/4 x 20	0.43 11	0.63 16	0.71 18	0.94 24	1.22 31	1.46 37	0.43 11	0.75 19	0.94 24	1.26 32	1.46 37	0.55 14	0.79 20	0.39 10
1.57 40	5/16 x 18	0.79 20	0.91 23	1.26 32	1.42 36	1.89 48	-	0.67 17	0.94 24	1.42 36	1.89 48	-	0.71 18	0.98 25	0.51 13
1.97 50	3/8 x 16	0.98 25	1.18 30	1.57 40	1.69 43	2.17 55	-	0.98 25	1.18 30	1.69 43	2.17 55	-	0.87 22	1.26 32	0.67 17
2.48 63	1/2 x 13	-	-	-	-	-	-	0.75 19	0.98 25	1.97 50	-	-	1.02 26	1.57 40	0.83 21

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂	Length l ≈																	d ₃	h ₁	h ₂											
		GN 6336.4 ST										GN 6336.5 ST																				
25 0.98	M 5	10 0.39	15 0.59	20 0.79	25 0.98	30 1.18	-	-	-	-	-	-	-	-	-	-	-	10 0.39	15 0.59	20 0.79	25 0.98	-	12 0.47	16 0.63	8 0.31							
25 0.98	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	45 1.77	60 2.36	-	-	-	-	-	-	-	-	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	-	12 0.47	16 0.63	8 0.31						
32 1.26	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	45 1.77	60 2.36	0.63	0.79	0.98	1.18	1.38	1.77	0.39	0.63	0.79	0.98	1.18	0.39	0.63	0.79	0.98	1.18	0.55	0.79	0.39				
32 1.26	M 8	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	55 2.17	-	-	-	-	-	-	20 0.79	25 0.98	30 1.18	40 1.57	-	-	-	-	-	14 0.55	20 0.79	10 0.39					
40 1.57	M 8	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	55 2.17	0.63	0.79	0.98	1.18	1.57	2.17	0.79	0.98	1.18	1.57	0.79	0.98	1.18	1.57	0.79	0.98	1.18	1.57	0.71	0.98	0.51		
40 1.57	M 10	15 0.59	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	45 1.77	55 2.17	-	-	-	-	-	-	20 0.79	25 0.98	30 1.18	45 1.77	55 2.17	-	-	-	-	18 0.71	25 0.98	13 0.51					
50 1.97	M 10	15 0.59	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	45 1.77	55 2.17	0.98	1.18	1.38	1.77	2.17	0.79	0.98	1.18	1.77	2.17	0.79	0.98	1.18	1.77	2.17	0.79	0.98	1.18	1.77	2.17	0.87	1.26	0.67
50 1.97	M 12	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	60 2.36	-	-	-	-	-	-	30 1.18	40 1.57	50 1.97	-	-	-	-	-	-	22 0.87	32 1.26	17 0.67						
63 2.48	M 12	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	60 2.36	-	1.18	1.38	1.57	1.97	2.36	1.18	1.57	1.97	-	-	30 1.18	40 1.57	50 1.97	-	-	26 1.02	40 1.57	21 0.83					
80 3.15	M 16	-	-	-	-	-	-	-	-	30 1.18	40 1.57	50 1.97	60 2.36	70 2.76	-	-	-	-	-	-	-	-	-	-	35 1.38	50 1.97	25 0.98					

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

