



SIMATIC PM1207/1AC/24VDC/2.5A

SIMATIC S7-1200 Power Module PM1207 Stabilized power supply input: 120/230 V AC, output: DC 24 V/2,5 A

Input	
type of the power supply network	1-phase AC
supply voltage at AC	
• initial value	Automatic range selection
supply voltage	
• 1 at AC rated value	120 V
• 2 at AC rated value	230 V
input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	176 ... 264 V
design of input wide range input	No
overvoltage overload capability	2.3 × Vin rated, 1.3 ms
operating condition of the mains buffering	at Vin = 93/187 V
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at Vin = 93/187 V
line frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	1.2 A
• at rated input voltage 230 V	0.67 A
current limitation of inrush current at 25 °C maximum	13 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I ² t value maximum	0.5 A ² ·s
fuse protection type	T 3,15 A/250 V (not accessible)
• in the feeder	Recommended miniature circuit breaker: 16 A characteristic B or 10 A characteristic C
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	0.2 %
residual ripple	

<ul style="list-style-type: none"> • maximum 	150 mV
voltage peak	
<ul style="list-style-type: none"> • maximum 	240 mV
product function output voltage adjustable	No
type of output voltage setting	-
display version for normal operation	Green LED for 24 V OK
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	6 s; 2 s at 230 V, 6 s at 120 V
voltage increase time of the output voltage	
<ul style="list-style-type: none"> • typical 	10 ms
output current	
<ul style="list-style-type: none"> • rated value • rated range 	2.5 A 0 ... 2.5 A
supplied active power typical	60 W
short-term overload current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up typical • at short-circuit during operation typical 	6 A 6 A
duration of overloading capability for excess current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up • at short-circuit during operation 	100 ms 100 ms
product feature	
<ul style="list-style-type: none"> • bridging of equipment 	Yes
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	83 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	12 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.3 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	3 %
setting time	
<ul style="list-style-type: none"> • load step 50 to 100% typical • load step 100 to 50% typical 	5 ms 5 ms
setting time	
<ul style="list-style-type: none"> • maximum 	5 ms
Protection and monitoring	
design of the overvoltage protection	< 33 V
response value current limitation typical	2.65 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
<ul style="list-style-type: none"> • typical 	2.7 A
display version for overload and short circuit	-
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> • maximum 	3.5 mA
protection class IP	IP20
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking • UL approval 	Yes Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-Recognized (UL 60950-1, CSA C22.2 No. 60950-1) File E151273
<ul style="list-style-type: none"> • CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259;

<ul style="list-style-type: none"> • cCSAus, Class 1, Division 2 • ATEX 	cURus-Recognized (UL 60950-1, CSA C22.2 No. 60950-1) File E151273 No Yes; ATEX (EX) II 3G Ex nA nC IIC T4 Gc
certificate of suitability <ul style="list-style-type: none"> • relating to ATEX 	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus (ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
<ul style="list-style-type: none"> • IECEX • NEC Class 2 • ULhazloc approval • FM registration 	Yes; IECEX Ex nA nC IIC T4 Gc No Yes Yes; Class I, Div. 2, Group ABCD, T4
type of certification CB-certificate	Yes
certificate of suitability <ul style="list-style-type: none"> • EAC approval 	Yes
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	ABS, BV, DNV GL, LRS, NK
Marine classification association <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) 	Yes Yes Yes Yes Yes
EMC	
standard <ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class B not applicable EN 61000-6-2
environmental conditions	
ambient temperature <ul style="list-style-type: none"> • during operation • during transport • during storage 	0 ... 60 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	screw-type terminals L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² L+, M: 2 screw terminals each for 0.5 ... 2.5 mm ² -
width of the enclosure	70 mm
height of the enclosure	100 mm
depth of the enclosure	75 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	20 mm 20 mm 0 mm 0 mm
net weight	0.3 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15, wall mounting
MTBF at 40 °C	1 492 537 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

