ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב		m		0		
4	ØS					4
				LAYOUT SHOWN AS EXA	MPLE	3
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Coni Dim	nector dimension Nominal				
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minin	ØS Z VV THRE	35.7 Max 31 Max		SOURIAU shall not be liable for any n due to a use of the Products which the Specifications issued by either of th (professional recommendation Country FR	h does not comply with ne Parties or by a third party	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D517W22SB			
-Temperature Range <u>-</u> -65°C to +175°C			A 17-10-2016	First Release		
-Salt Spray : 500 hours			ISS DATE	Latest modification - by	1	MOD N°
			Designed By:	Date:	CUSTOMER DRAWING	
			TITLE	Aluminiu	Im Plug 8D series	
BASIC SERIES: 8D 5 - 17 SHELL TYPE : Plug with RFI Shielding	7 W 22 S B		SCALE	General linear Tolerances:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17		ORIENTATION : B ONTACT TYPE : SOCKET(500 Matings)	SOURIAU		This document is the property SOURIAU it must not be reproduced o communicated without permis	or
PLATING : W = Olive drab Cadmium		CONTACT LAYOUT : 17-22	FORMAT	SOURIAU E	DRG N°	SHEET
			A3	8D517W2	25B-C	1/2

	т	۵	г	m	D	0
4		Contact Layout 22				
 	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0				
						SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen
					A 17-10-20 ISS DATE Designed By:	PN: 8D51
					TITLE SCALE NA SOURIA	
	Н	G	F	E	D	SOURIA 8D517 C

