

## Cisco-Compatible SFP-10G-LRM SFP+ Transceiver - 10GBase-LRM, DDM, Multimode LC, 1310 nm, 220 m (721 ft.)

MODEL NUMBER: N286-10G-LRM



Links a multimode Gigabit Ethernet network cable to a Cisco router, server or switch's SFP port.

### Features

**SFP+ Transceiver Designed for Connection to Your Cisco Network Switch or Server** This SFP+ transceiver allows you to connect a 50/125 multimode fiber optic cable to a 10 Gbps network router, server or switch. It transmits data up to 220 meters (721 feet) and supports bi-directional Gigabit Ethernet communication up to 11.1 Gbps. The metal housing protects against electromagnetic interference (EMI) and excessive power dissipation.

**Functionally Equivalent to Cisco SFP-10G-LRM Transceiver Module** The MSA-compliant N286-10G-LRM functions just like the equivalent Cisco SFP-10G-LRM transceiver module and is manufactured to meet or exceed Cisco specifications. You can use this transceiver with any compatible Cisco router, server or switch and receive the same performance as the SFP-10G-LRM.

**Hot-Swappable for Installation Without Network Interruption** This input/output device is fully hot-swappable, so you can install it without a potentially costly 10 Gbps network shutdown or device reboot. Just plug the SFP+ end of the transceiver into your Cisco network device. The other end has an LC duplex connector to link with multimode fiber optic cable (sold separately). A convenient bail clasp latch helps you carefully remove the module from the device.

**Supports Digital Diagnostic Monitoring (DDM) for Real-Time Status Monitoring** DDM support lets you keep track of various operating statuses in real time, including transceiver temperature, input and output power, and supply voltage.

## Specifications

OVERVIEW	
UPC Code	037332249272
Brand Compatibility	Cisco

### Highlights

- SFP+ transceiver module 100% compatible with Cisco's equivalent module
- Provides 10 Gbps throughput up to 220 m (721 ft.) via multimode fiber cabling
- LC duplex female connector supports 10GBase-LRM signal at 1310 nm wavelength
- Hot-swappable interface lets you install and uninstall without shutting down
- Supports DDM for monitoring temperature and other real-time operating parameters

### Applications

- Install an additional LC duplex port on a Cisco router, server or switch for the purpose of connecting a multimode Gigabit Ethernet network cable

### System Requirements

- Cisco or other compatible network router, server or switch

### Package Includes

- N286-10G-LRM Cisco-Compatible SFP-10G-LRM SFP+ Transceiver
- Quick Start Guide



<b>PHYSICAL</b>	
Unit Dimensions (hwd / in.)	0.49 x 2.3 x 0.55
Unit Weight (kg)	0.03
Unit Weight (lbs.)	0.064
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	23 to 185°F (-5 to 85°C)
Storage Temperature Range	-40 to 185°F (-40 to 85°C)
Relative Humidity	5% to 85% RH, Non-Condensing
Operating Temperature	23 to 185°F (-5 to 85°C)
<b>COMMUNICATIONS</b>	
Network Compatibility	10 Gbps
Wavelength	1310nm
Transmission Distance	220 m
<b>CONNECTIONS</b>	
Side A - Connector 1	SFP+ (MALE)
Side B - Connector 1	LC DUPLEX (FEMALE)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Optical Port	LC
Multi-Source Agreement (MSA) Compliant	Yes
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>