



## Seeed Tiny BLE - BLE + 6DOF Mbed Platform

SKU 102080005

Seeed Tiny BLE is a Bluetooth Low Energy development board designed with low energy consumption and small size in mind. It's integrated with current measurement feature to provide real time energy consumption data, which is essential for developers to optimize software to design long battery life devices. It supports ARM mbed cloud-based IDE with an handy C/C++ SDK and a large number of open source libraries, which makes prototyping and development extremely easy.

With its modular design, we can divide it into two parts - CMSIS DAP interface part and BLE part. The CMSIS DAP interface part is like the Swiss army knife. It provides drag-n-drop programming, CMSIS DAP debug, USB virtual serial port, current measurement and battery charging. The BLE part is built on the Nordic nRF51822 with Bluetooth Low Energy 2.4GHz multiprotocol radio and a 32 bit ARM Cortex-M0 core running 16MHz. MPU6050, a 6 DOF with 3D accelerometer and 3D gyroscope, is integrated to provide motion detect feature.

### Features

- nRF51822: ARM Cortex-M0 + 2.4GHz radio (BLE or ANT+)
- MPU-6050:3d accelemeter + 3d gyroscope
- LPC111U35FHI33:CMSIS DAP
- Current measurement
- CN3065:battery charge port on USB part
- Power supply:USB/battery(3.5-4.2V)
- Output voltage:3.3V
- 4 I/Os, all can be used as analog input, digital input/output, I2C, SPI or UART
- VCC output control

## Technical Details

Dimensions	43mm x 29mm x 4.30mm
Weight	G.W 6g
Battery	Exclude
Microcontroller	nRF51822QFAA; LPC11U35FHI33
Power supply	USB/Battery

## *Part List*

Seed Tiny BLE - BLE + 6DOF Mbed Platform	1
--	---

## *ECCN/HTS*

ECCN	3A991.a
HSCODE	8471504090

