






| ISSUE NUMBER |  |
|--------------|--|
| ORIGINAL     |  |







.XX ±0.13


.XXX ±0.05



## NOTES:

| MATERIAL:<br>HOUSING:<br>SHELL:<br>CONTACT: | THERMOPLASTIC POLYES<br>STEEL, TIN PLATED<br>COPPER ALLOY, 30µ GOLE |  |
|---|---|--|
| OPERATING TEMPERATURE:                      | -55°C ~ 125°C   |  |
| POWER/CO-AX CONTACT RATING:<br>(IF PRESENT) | 30A (CURRENT)   |  |
| SIGNAL CONTACT CURRENT RATING:              | 5A PER CONTACT<br>10mΩ MAX.   |  |
| INSULATOR RESISTANCE:                       | 5000MΩ min.   |  |
| DIELECTRIC<br>WITHSTANDING VOLTAGE:         | 1000V AC rms  |  |

|  |  |                         | SW REFERENCE NO.: 630 COMBO ASSEMBLY |       |  |  |
|--|--|-------------------------|--------------------------------------|-------|--|--|
| COMBINATION D-SUB  |  | DRAWN: C.B              | DATE: JAN. 01/20                     | 19    |  |  |
|  |  | CHECKED:                | DATE:                                |       |  |  |
| EDAG INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)  | SHEET 1 OF                           | 2     |  |  |
|  |  | DRAWING NUMBER: 630-5W1 | -640-3T3                             | ISSUE |  |  |
|  |  | PART NUMBER: 630-5W1    | -640-3T3                             | 1     |  |  |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



