



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 38.62 g ± 10%

| Connector dimension | |
|---------------------|-----------------|
| Dim | Nominal |
| A | 44.5±0.3 |
| B | 30.15+0.1/-0.15 |
| R | 32.5Max |
| S | 41.3±0.4 |
| W | 2.2+0.9/-0.1 |
| VV THREAD | M25x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D717W99PD

| | | | |
|---------------------|---------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------|
| A | 01-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| NA | | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| SOURIAU | WWW.SOURIAU.COM | | |
| FORMAT A3 | SOURIAU DRG N° 8D717W99PD-C | | SHEET 1/2 |

BASIC SERIES: 8D | 7 | - | 17 | W | 99 | P | D

SHELL TYPE : Jam nut Receptacle

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 17

PLATING : W = Olive drab Cadmium

ORIENTATION : D

CONTACT TYPE : PIN(500 Matings)

CONTACT LAYOUT : 17-99

Contact Layout



| Contacts (Insert arrangement 17-99) | | | | | |
|----------------------------------------|------------------|--------------|---------------------|------------------|--------------|
| Contact position ID | Contact location | | Contact position ID | Contact location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | .000 (0.00) | +321 (8.15) | N | -305 (7.75) | +099 (2.51) |
| B | +131 (3.33) | +293 (7.44) | P | -239 (6.07) | +214 (5.44) |
| C | +239 (6.07) | +214 (5.44) | R | -131 (3.33) | +293 (7.44) |
| D | -.305 (7.75) | -.099 (2.51) | Q | -.070 (1.78) | -.177 (4.50) |
| E | +319 (8.10) | -.034 (0.86) | T | +070 (1.78) | +177 (4.50) |
| F | +278 (7.06) | -.161 (4.09) | U | +175 (4.45) | +094 (2.39) |
| G | +189 (4.80) | -.260 (6.60) | V | +150 (3.81) | -.075 (1.91) |
| H | +.067 (1.70) | -.314 (7.98) | W | +000 (0.00) | -.161 (4.09) |
| J | -.067 (1.70) | -.314 (7.98) | X | -.150 (3.81) | -.075 (1.91) |
| K | -.189 (4.80) | -.260 (6.60) | Y | -.175 (4.45) | +094 (2.39) |
| L | -.278 (7.06) | -.161 (4.09) | Z | +000 (0.00) | +025 (0.64) |
| M | -.319 (8.10) | -.034 (0.86) | | | |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact position ID | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|---------------------|------------|
| 17 | -99 | 2 21 | 16 20 | I | W,Z All others | MS20053-99 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal |
|-----|---------------|
| B | 30.73+0/-0.25 |
| ØC | 32.01+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D717W99PD

| | | | |
|---------------------|------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------|
| A | 01-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT A3 | SOURIAU DRG N° 8D717W99PD-C | | SHEET 2/2 |