



SS Stainless Steel

Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ Thread GN 432	d ₃	b	h	t min.
.98 25	1/4 x 20	.31 8	.31 8	.39 10	.28 7
1.18 30	5/16 x 18	.39 10	.39 10	.47 12	.35 9
1.42 36	3/8 x 16	.47 12	.47 12	.57 14.5	.39 10

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² d ₂ Thread GN 432 / GN 431	³ Length l				d ₃	b	h	t min.
25 .98	M 6	16 .63	20 .79	25 .98	-	8 .31	8 .31	10 .39	7 .28
30 1.18	M 6	16 .63	20 .79	25 .98	-	10 .39	10 .39	12 .47	7 .28
30 1.18	M 8	16 .63	20 .79	25 .98	32 1.26	10 .39	10 .39	12 .47	9 .35
36 1.42	M 8	16 .63	20 .79	25 .98	32 1.26	12 .47	12 .47	14.5 .57	9 .35
36 1.42	M 10	20 .79	30 1.18	40 1.57	-	12 .47	12 .47	14.5 .57	7 .28

Specification

- Wing body
Stainless steel, sintered
European Standard No. 1.4404 (AISI 316 LHC)
Matte shot-blasted finish
- Threaded stud
Stainless steel
European Standard No. 1.4301 (AISI 304)
- Matte shot-blasted finish
- Screwed in and secured by a cross-dowel pin
- RoHS compliant

Information

Where a greater torque is required GN 432 wing nuts and GN 431 wing screws are a better solution than knurled nuts.

see also...

- Wing Nuts GN 834 (Stainless Steel)
- Wing Screws GN 835 (Stainless Steel)

How to order (Inch wing nut) ¹ ² GN 432-36-3/8X16	1	Handle diameter d ₁
	2	Thread d ₂

How to order (Metric wing screw) ¹ ² ³ GN 431-25-M6-20	1	Handle diameter d ₁
	2	Thread d ₂
	3	Length l