



RUGGED KEYBOARD

Designed for Public Safety
and Mobile Data
Applications

SPECIFICATIONS

- Storage Temperature: -55C to +85C
- Operating Temperature: -40C to +70C
- Operating Humidity: 50% to 90%
- Dimensions: 12.00 x 6.00 x 1.50 in (340.80 x 152.40 x 38.10 mm)
- Weight: 2 lbs

FEATURES

- 86 Keys
- Coiled Cord
- Rubber
- LED Backlighting - Rated for the Life of the Product (200,000 hr. LED's)
- Rugged Integrated Pointing Device
- Special "Emergency" Key, When Pressed, Sends a Signal of Shift + F1 and is Illuminated Brighter Than Other Keys for 15 Seconds
- Fully Customizable
- Low Cost, Low Profile With Full Size Keys
- Tactile Feedback
- 5 Million Actuations Per Key

ELECTRICAL SPECIFICATIONS

- Voltage: +5Vdc From Data Cord
- Radiated Immunity: 20 Volts / Meter
- Backlight Dimming Includes 8 Levels of Intensity Controlled by "Fn" + "0" - "7"

COMPLIANT

- NEMA 4
- UL60950
- CE
- FCC Class B

INTERFACE

USB

TG3 PART NUMBER	DESCRIPTION
KBA-BLH-5RU	Black, Rubber, USB, Coiled Cord, Red Backlight