


Material Declaration for M80-5000000M5-10-334-00-000

Product Information	
Part Number:	M80-5000000M5-10-334-00-000
Part Description:	Datamate Mix-Tek Male Horizontal
Part Weight (g):	7.163

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Power Contact - Beryllium Copper	4.658	4%	Copper	7440-50-8
	0.0906	2%	Beryllium	7440-41-7
	0.0191	2%	Lead	7439-92-1
	0	0.0143g max	Nickel (impurity only)	7440-02-0
	0	0.0143g max	Cobalt (impurity only)	7440-48-4
	0	0.00954g max	Iron (impurity only)	7439-89-6
	0	0.00954g max	Aluminium (impurity only)	7429-90-5
	0	0.00954g max	Silicon (impurity only)	7440-21-3
	0	0.0238g max	Other Impurities	
Power Contact - Plating	0.00777	5%	Gold	7440-57-5
	0.0192	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.641	10%	Iron	7439-89-6
	0.159	4%	Chromium (Metallic)	7440-47-3
	0.0793	4%	Nickel	7440-02-0
	0.00617	0.8%	Copper	7440-50-8
	0.0022	0.5%	Sulphur	7704-34-9
	0	0.00106g max	Carbon (impurity only)	7440-44-0
	0	0.00881g max	Silicon (impurity only)	7440-21-3
	0	0.0176g max	Manganese (impurity only)	7439-96-5
	0	0.000528g max	Phosphorus (impurity only)	7723-14-0
	0	0.00881g max	Molybdenum (impurity only)	7439-98-7
	0	0.00176g max	Niobium (impurity only)	7440-03-1
	0	0.000882g max	Titanium (impurity only)	7440-32-6
Jackscrew Bolts - Stainless Steel	0.326	10%	Iron	7439-89-6
	0.0806	4%	Chromium (Metallic)	7440-47-3
	0.0403	4%	Nickel	7440-02-0
	0.00313	0.8%	Copper	7440-50-8
	0.00112	0.5%	Sulphur	7704-34-9
	0	0.000538g max	Carbon (impurity only)	7440-44-0
	0	0.00448g max	Silicon (impurity only)	7440-21-3
	0	0.00896g max	Manganese (impurity only)	7439-96-5
	0	0.000268g max	Phosphorus (impurity only)	7723-14-0
	0	0.00448g max	Molybdenum (impurity only)	7439-98-7
	0	0.000896g max	Niobium (impurity only)	7440-03-1
	0	0.000448g max	Titanium (impurity only)	7440-32-6
Moulding (total weight)	1.03	10%	30% Glass-Filled PPS	
Containing:	0.721	10%	PPS	26125-40-6
	0.309	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

