

Thermal Pad 21-250

Version TDS.21-250.V.B.0

Description

Through innovative technology, this soft and conformable thermal pad is designed to provide high level of thermal performance with minimum pressure on electronic components.



Typical Properties

Properties	Thermal Pad 21-250	Test Method	
Thermal	Thermal Conductivity (W/m-K)	5	
	Continuous Use Temp. (°C)	-55~200	
Physical	Color	Grey	
	Substrate	Silicone	
	Density (g/cm ³)	2.78	
	Thickness Range (mm)	0.5~5	
	Thickness Tolerance	> 1mm	±10%
		≤/ = 1mm	±0.1mm
Hardness (shore 00)	50	ASTM D2240	
Electrical	Dielectric Breakdown Voltage (KVAC/mm)	>3	
	Dielectric Constant@1MHz	4.33	
	Volume Resistivity (ohm-cm)	>10 ¹³	
Regulatory	Flame Rating	V0	
	RoHS Compliant	YES	
	Shelf Life (months)	24	


Benefits

- Extremely Good Thermal Performance
- Very Good Compression
- High Breakdown Voltage
- Easy For Installation
- RoHS Compliant

Applications


- Memory Modules
- Mass Storage Devices
- Automotive Electronics
- Telecommunication Hardware
- Radios
- Power Electronics
- Set-Top Boxes
- Audio And Video Players
- IT Infrastructure

Compression Deflection



21-250Gap Pad 1.0mm thick;
1 inch² test sample;
Rate of strain = 1.0 mm/min

Thermal Resistance VS Compression



21-250 Gap Pad 1.0mm thick;
1 inch² test sample;
Pressure step = 10psi

Recommended Compression
Standard Size
Storage Requirement

20%~30%
16" X 8" (406mmX203mm)
Room Temperature Between 20 to 25 degree
R.H. 50%

Disclaimers

- The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the issuing date of this TDS. When using our products, no matter what type of equipment they might be used for, be sure to make a written agreement on the specifications with us in advance. The design and specifications in this TDS are subject to change without prior notice.
- Do not use the products beyond the specifications described in this TDS. This TDS explains the typical performance of the products as individual component. Before use, check and evaluate their operations when installed in your products.
- Install the following systems for a failsafe design to ensure safety if these products are to be used in equipment where a defect in these products may cause the loss of human life or other significant damage, such as damage to vehicles (automobile, train, vessel), traffic lights, medical equipment, aerospace equipment, electric heating appliances, combustion/gas equipment, rotating equipment, and disaster/crime prevention equipment.

