


WIRING SCHEMATIC

CONNECTOR SPECIFICATION:

VOLTAGE RATING	300 V
AMPERAGE RATING	max. 4 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	FLEXING: -5°C TO +70°C STATIC: -30°C TO +70°C

ITEM	COMPONENT	MATERIAL	FINISH
7	LABLE	MYLAR	BLACK/YELLOW
6	O-RING	VITON	RED
5	COUPLER	BRASS	NICKEL PLATED
4	PIN CONTACT	COPPER ALLOY	GOLD OVER NICKEL
3	INSERT	PUR	BLACK
2	OVERMOLD	TPE	YELLOW
1	CABLE #22-3 (COPPER STRANDING) 4 CONDUCT. 300V	JACKET: TPE	YELLOW



MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH
1200680211	884A31K05M003	0.98' +0.75" -0 [0.3M +19.1 -0]

DESCRIPTION EC NO: WEU2010-0362 DRWN: BBRAUCH 2010/02/15 CHK'D: NS APPR: NSTAUDIG 2010/02/18	QUALITY SYMBOLS ▽ = 0 ▽/C = 0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±0.1 1 PLACE ±0.3 ±--- ANGULAR ± --- °	DIMENSION STYLE IN/MM DRAWN BY DATE BBRAUCH 2010/02/15 CHECKED BY DATE NS 2010/02/16 APPROVED BY DATE NSTAUDIG 2010/02/18	SCALE 2:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION	MIC INL. SPLITTER XM 3P FE 90(2X) TO 4P M
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	MATERIAL NO. SD-120068-027 DOCUMENT NO.	SHEET NO. 1 OF 1
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
	SIZE A3				