
т	۵	н т	т	D	0







LAYOUT SHOWN AS

Keying Shown as example

F

CHARACTERISTICS

SHELL SIZE : 25

PLATING : F = Nickel

Н

ω

-Standard : Based on MIL-DTL-38999 Series III

		: Aluminium P	
	-Shell Plating	: Nickel R1	+
	-Insulator	: Thermoplastic R2	
	-Contacts	: Copper Alloy	
	-Seals & Grommet	: Silicon Elastomer W	2
\sim	-Contact Plating	: Gold over copper Alloy 0.8µm minimum Z	
	-Durability	: 500 Mating cycles VV THREAD)
	-Delivered with Souria	u contacts and Accessories	
	-Temperature Range	65°C to +200°C	
	-Salt Spray	· : 48 hours	
	-Mass	: 51.42 g ± 10%	
	BASIC SERIES:	8D 0 - 25 F 29 A N	
→	SHELL TYPE : Square	Flange Receptacle	
	CONTACT TYPE : Sta	andard Crimp Contact	

G

Dim	Nominal	
Р	3.91±0.2	
PP	6.15±0.2	
R1	38.1	
R2	34.93	
S	46±0.3	
V	20.07+0/-1.25	
W	2.1/3.2	
Z	31.5 Max	
/V THREAD	M37x1-6g	

ORIENTATION : N

D

CONTACT TYPE : PIN(500 Matings)

Е

CONTACT LAYOUT : 25-29

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment



Ξ		А		_		
				4		
AS EXAMPLE				3		
any non-conformi which does not co or of the Parties or adation, technical n	omply with by a third par otice.)	ty				
Intry Juriso	diction & Con Not Listed	trol List		2		
5F29AN						
	CUSTOME	R DRAWING	MOD N°			
um Receptac	n Receptacle 8D series					
ar		[/] PROJECT		1		
COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N°	1		SHEET			
F29AN-C B		A	1/2	J		

