

C878BF34300AA4J

C87, Film, Film/Foil Polypropylene, Motor Run, 3 uF, 5%, 470 VAC

Click [here](#) for the 3D model.

Dimensions

D 30mm +1mm

L 48mm +/-2mm

Packaging Specifications

Mounting Bolt - M8x10

Packaging Bulk, Bag

Packaging Quantity 115

General Information

Series C87

Dielectric Film/Foil Polypropylene

Style Can

Description Aluminum Case, Plastic Cover, Spun Seal

Features Spun Seal, Safety Class S2, UL_94 V0 Disk

RoHS Yes

Lead Fast On (2+2)

Qualifications UL, VDE, CQC, CSA (470 VAC), UL_94 V0 Disk

AEC-Q200 No

Component Weight 36 g

Specifications

Capacitance 3 uF

Capacitance Tolerance 5%

Voltage AC 470 VAC

Temperature Range -25/+85°C

Rated Temperature 85°C

Max dV/dt 20 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - c3b6ee67-64bb-4013-8ea3-3c966fea15d0

© 2006 - 2023 KEMET

Generated 5/18/2023 - c3b6ee67-64bb-4013-8ea3-3c966fea15d0

© 2006 - 2023 KEMET