



Main

Range of Product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or Component Type	Lamp
Device Application	Multi-purpose
Device composition	1 lamp 1 cable 1 fixed base
Power factor	0.9

Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120 V AC 50/60 Hz
Bulb base	E27
Bulb type	LED
Control Type	Built-in recessed switch
Luminous flux	1100 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable 9.84 ft (3 m) supplied
Fixing Mode	Screws Adhesive
Range compatibility	Spacial Thalassa
Material	PC (UL94 V-0)
Height	15.89 in (403.5 mm)
Width	3.60 in (91.5 mm)
Depth	2.60 in (66 mm)
Color	Black RAL 9005)

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical Insulation Class	Class II
Standards	IEC 60598 UL 94
Ambient Air Temperature for Operation	3...149 °F (-16...65 °C)
Ambient Air Temperature for Storage	14...140 °F (-10...60 °C)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606481190390
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	4.33 in (11.0 cm)
Package 1 Length	14.57 in (37.0 cm)
Package 1 Weight	31.11 oz (882.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.45 in (24.0 cm)
Package 2 Width	14.96 in (38.0 cm)
Package 2 Length	16.73 in (42.5 cm)
Package 2 Weight	20.75 lb(US) (9.41 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.