

GJM1555C1H5R8DB01J

Note: This datasheet may be out of date. Please download the latest datasheet of GJM1555C1H5R8DB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM1555C1H5R8DB01%23

#### "#" indicates a package specification code.



< List of part numbers with package codes > GJM1555C1H5R8DB01D GJM1555C1H5R8DB01W

# Ар

## Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	performance and reliability of the actual	
	performance and reliability of the actual Product.	

### GJM1555C1H5R8DB01J




# PackagingSpecificationsStandard<br/>Packing<br/>QuantityDφ180mm Reel Paper Tape10000Wφ180mm Reel W8P1 Paper<br/>Tape20000Jφ330mm Reel Paper Tape50000

Mass (typ.)	
1 piece	1.6mg

## Appearance & Shape





1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





## GJM1555C1H5R8DB01J

Note: This datasheet may be out of date. Please download the latest datasheet of GJM1555C1H5R8DB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM1555C1H5R8DB01%23

#### "#" indicates a package specification code.



## Specifications

Length	1.0±0.05mm
Width	0.5±0.05mm
Thickness	0.5±0.05mm
Capacitance	5.8pF ±0.5pF
Distance between external terminals g	0.3mm min.
External terminal size e	0.15 to 0.35mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	50Vdc
Size code in inch(mm)	0402 (1005M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

#### 2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.