

28179.6 PVC-TAA 15X67 K GR

Device and installation marker, Length: 67 mm, Width: 15 mm, Colour: grey

RAL: Ähnlich 7035

Business data

Article number	28179.6
Article name	PVC-TAA 15X67 K GR
GTIN (EAN)	4044211213312
Packaging unit	70
Quantity unit	PC
Number of markers per card	7 ST
Weight per piece (not including packaging)	2.85 g
Weight per piece (including packaging)	2.85 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28179.7
Product description	Device and installation marker

Technical data

Dimensions

Length	67 mm
Width	15 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0, V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C, 10 °C
Processing temperature, max.	40 °C, 40 °C
Silicone-free	✓ ✓

Further technical data

Mounting	Self-adhesive
Software code	968

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST