## ATGBICS Universally Coded MSA Compliant Transceiver SFP 2G Fibre Channel (850nm, MMF, 300m, DOM)

Brand : ATGBICS

Product code: SFP-2G-FC-SW-MSA-AT



Product name : ATGBICS Universally Coded MSA Compliant Transceiver SFP 2G Fibre Channel (850nm, MMF, 300m, DOM)

ATGBICS Universally Coded MSA Compliant Transceiver SFP 2G Fibre Channel (850nm, MMF, 300m, DOM)

ATGBICS Universally Coded MSA Compliant Transceiver SFP 2G Fibre Channel (850nm, MMF, 300m, DOM):

ATGBICS SFP-2G-FC-SW-MSA-AT Universally Coded MSA Compliant 2GBase-SW fibre Channel supports a distance of up to 300m over multi mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets all Multi-Source Agreement (MSA) standards for this form factor and are uniquely serialised for full date code and BOM traceability. We proudly offer a compatibility guarantee and lifetime replacement warranty.


Ro	Н
κυ	2002/95/EC

Performance		Feature
SFP transceiver type *	Fiber optic	Certifica
Maximum data transfer rate *	2000 Mbit/s	Power
Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector	SFP ★ ↓ LC	Input vo Maximu Power c
SFP transceiver standard	SW	Operati
Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM)	300 m 850 nm ✓ 2.5 Gigabit Ethernet ✓	Maximu Operatin Storage Operatin Storage <b>Weight</b> Width
Features		Depth
Product colour Housing material	Silver Metal	Height Weight
Plug and Play	√	Packag
Hot-Plug support	<	Number

Plug and Play
Hot-Plug support
Hot-swap
Easy to install
Country of origin
Brand compatibility

Metal
1
1
1
1
United Kingdom
MSA Compliant

Features	
Certification	CE, FCC, RoHS
Power	
Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
Operational conditions	
Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%
Weight & dimensions	
Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 15 g
Packaging data	
Number of products included Package type	1 pc(s) Box
Technical details	
Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468773920

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.