

## P-Channel Power MOSFET

-60V, -14.5A, 68 mΩ

### FEATURES

- Improved dV/dt capability
- Fast switching
- 100% Eas Guaranteed
- Pb-free plating
- RoHS compliant
- Halogen-Free according to IEC 61249-2-21


PRODUCT SUMMARY			
PARAMETER	VALUE	UNIT	
$V_{DS}$	-60	V	
$R_{DS(on)}$ (max)	$V_{GS} = -10V$	68	mΩ
	$V_{GS} = -4.5V$	110	
$Q_g$	$V_{GS} = -10V$	18	nC

### APPLICATIONS

- Motor Drive
- Power Tools
- LED Lighting



TO-251S (IPAK SL)



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	$V_{DS}$	-60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>(Note 1)</sup>	$I_D$	$T_C = 25^\circ\text{C}$	-14.5
		$T_C = 100^\circ\text{C}$	-9.2
Pulsed Drain Current <sup>(Note 2)</sup>	$I_{DM}$	-58	A
Single Pulse Avalanche Current <sup>(Note 3)</sup>	$I_{AS}$	-19.1	A
Single Pulse Avalanche Energy <sup>(Note 3)</sup>	$E_{AS}$	18.2	mJ
Total Power Dissipation	$P_D$	20.5	W
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$

THERMAL RESISTANCE			
PARAMETER	SYMBOL	MAXIMUM	UNIT
Thermal Resistance – Junction to Case	$R_{\theta JC}$	6.1	$^\circ\text{C/W}$
Thermal Resistance – Junction to Ambient	$R_{\theta JA}$	62	$^\circ\text{C/W}$

**Notes:**  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.  $R_{\theta JA}$  shown below for single device operation on FR-4 PCB in still air.

<b>ELECTRICAL CHARACTERISTICS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
<b>Static</b> (Note 4)						
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{V}, I_D = -250\mu\text{A}$	$BV_{DSS}$	-60	--	--	V
Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = -250\mu\text{A}$	$V_{GS(TH)}$	-1.2	-1.4	-2.2	V
Gate-Source Leakage Current	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$	$I_{GSS}$	--	--	$\pm 100$	nA
Drain-Source Leakage Current	$V_{GS} = 0\text{V}, V_{DS} = -60\text{V}$	$I_{DSS}$	--	--	-1	$\mu\text{A}$
	$V_{GS} = 0\text{V}, V_{DS} = -48\text{V}$ $T_J = 125^\circ\text{C}$		--	--	-10	
Drain-Source On-State Resistance (Note 3)	$V_{GS} = -10\text{V}, I_D = -6\text{A}$	$R_{DS(on)}$	--	53.2	68	m $\Omega$
	$V_{GS} = -4.5\text{V}, I_D = -3\text{A}$		--	67.4	110	
Forward Transconductance	$V_{DS} = -10\text{V}, I_D = -6\text{A}$	$g_{fs}$	--	15.3	--	S
<b>Dynamic</b> (Note 5)						
Total Gate Charge	$V_{GS} = -10\text{V}, V_{DS} = -30\text{V},$ $I_D = -6\text{A}$	$Q_g$	--	18	--	nC
Gate-Source Charge		$Q_{gs}$	--	2.8	--	
Gate-Drain Charge		$Q_{gd}$	--	3.2	--	
Input Capacitance	$V_{GS} = 0\text{V}, V_{DS} = -30\text{V},$ $f = 1.0\text{MHz}$	$C_{iss}$	--	929	--	pF
Output Capacitance		$C_{oss}$	--	68	--	
Reverse Transfer Capacitance		$C_{rss}$	--	55	--	
Gate Resistance	$f = 1.0\text{MHz}$	$R_g$	--	14	--	$\Omega$
<b>Switching</b> (Note 6)						
Turn-On Delay Time	$V_{GS} = -10\text{V}, V_{DS} = -30\text{V},$ $I_D = -1\text{A}, R_G = 6\Omega$	$t_{d(on)}$	--	6.7	--	nS
Rise Time		$t_r$	--	8.5	--	
Turn-Off Delay Time		$t_{d(off)}$	--	53	--	
Fall Time		$t_f$	--	35	--	
<b>Source-Drain Diode</b>						
Diode Forward Voltage (Note 4)	$V_{GS} = 0\text{V}, I_S = -1\text{A}$	$V_{SD}$	--	--	-1	V
Reverse Recovery Time	$I_S = -1\text{A},$ $di/dt = 100\text{A}/\mu\text{s}$	$t_{rr}$	--	11.9	--	nS
Reverse Recovery Charge		$Q_{rr}$	--	6.2	--	nC

**Notes:**

- Current limited by package
- Pulse width limited by the maximum junction temperature
- $L = 0.1\text{mH}, V_{GS} = -10\text{V}, R_G = 25\Omega,$  Starting  $T_J = 25^\circ\text{C}$
- Pulse test:  $PW \leq 300\mu\text{s},$  duty cycle  $\leq 2\%$
- For DESIGN AID ONLY, not subject to production testing.
- Switching time is essentially independent of operating temperature.


**ORDERING INFORMATION**

ORDERING CODE	PACKAGE	PACKING
TSM680P06CH X0G	TO-251S	75pcs / Tube


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current**




**Gate-Source Voltage vs. Gate Charge**



**On-Resistance vs. Junction Temperature**




**On-Resistance vs. Gate-Source Voltage**




**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Capacitance vs. Drain-Source Voltage**




**$BV_{DSS}$  vs. Junction Temperature**




**Maximum Safe Operating Area, Junction-to-Case**



**Source-Drain Diode Forward Current vs. Voltage**





**Normalized Thermal Transient Impedance, Junction-to-Case**




**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)




**Normalized gate threshold voltage vs Temperature**




**PACKAGE OUTLINE DIMENSIONS** (Unit: Millimeters)

**TO-251S**



**MARKING DIAGRAM**



- Y** = Year Code
- M** = Month Code
- O** =Jan   **P** =Feb   **Q** =Mar   **R** =Apr
- S** =May   **T** =Jun   **U** =Jul   **V** =Aug
- W** =Sep   **X** =Oct   **Y** =Nov   **Z** =Dec
- L** = Lot Code (1~9, A~Z)

## **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.