


B45197A, Tantalum, MnO2 Tantalum, 100 uF, 20%, 6.3 V, SMD, Molded, Low ESR, Surge Robust, 400 mOhms, 3528, Height Max = 2.1mm



General Information	
Supplier:	KEMET
Series:	B45197A
Dielectric:	MnO2 Tantalum
Style:	SMD Chip
Description:	SMD, Molded, Low ESR, Surge Robust
Features:	Low ESR, Surge Robust
RoHS:	Yes
Termination:	Tin
Notes:	Obsolete. Old Part Number [Obsolete] Was B45197A1107M209

Dimensions	
Footprint	3528
L	3.5mm +/-0.2mm
W	2.8mm +/-0.2mm
H	1.9mm +/-0.2mm
S	0.7mm +/-0.3mm
F	2.2mm +/-0.1mm
K	1.4mm TYP

Specifications	
Capacitance:	100 uF
Capacitance Tolerance:	20%
Voltage DC:	6.3 VDC (85C), 4.22 VDC (125C)
Temperature Range:	-55/+125C
Rated Temperature:	85C
Dissipation Factor:	8%
Failure Rate:	N/A
Resistance:	0.4 Ohms (100kHz)
Current:	460 mAmps (25C), 414 mAmps (85C), 184 mAmps (125C)
Leakage Current:	6.3 uA

Packaging Specifications	
Packaging:	T&R, 178mm
Packaging Quantity:	2000