



基板取付穴推奨寸法

(基板厚: t=1~1.6mm)  
 RECOMMENDED PC BOARD  
 HOLE DIMENSION  
 (THICKNESS: t=1~1.6mm)

注記  
 NOTE

- △ 適合ターミナル: 50034 8\*00  
 APPLICABLE TERMINAL: 50034 8\*00
- 2. 材料 ハウジング: ポリアミド, UL94V-0  
 色: ナチュラル(白)  
 MATERIAL HOUSING: POLYAMIDE, UL94V-0  
 COLOR: NATURAL(WHITE)
- 3. ELV 及び RoHS 適合品  
 ELV AND RoHS COMPLIANT.

28	30.4	51015	1500	15
26	28.4	▲	1400	14
24	26.4		1300	13
22	24.4		1200	12
20	22.4		1100	11
18	20.4		1000	10
16	18.4		0900	9
14	16.4		0800	8
12	14.4		0700	7
10	12.4		0600	6
8	10.4		0500	5
6	8.4		0400	4
4	6.4		0300	3
2	4.4		0200	2
B	A	ORDER No.		極致 NO. OF CKT

REVISED EC NO: J2012-0968 DRWN: KWASHIO 2012/01/18 CHKD: KASAKAWA 2013/04/09 APPR: Y0110 2013/04/10	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 8:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	10 UNDER	±0.2	DRAWN BY HIJIMA	DATE 1996/05/28	TITLE 2.0 BOARD IN CONN HSG			
	10 OVER 30 UNDER	±0.25	CHECKED BY MFUKUSHIMA	DATE 1996/05/28	MATERIAL NO. SEE CHART			
	30 OVER	±0.3	APPROVED BY	DATE	DOCUMENT NO. SD-51015-**-00			
	ANGULAR ±3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
REV	DESCRIPTION					SHEET NO. 1 OF 1		