



General Information	
Series	C4AE_Press_Fit
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Component Weight	77.78 g
Notes	Not For New Design.

Specifications	
Capacitance	20 uF
Capacitance Tolerance	5%
Voltage DC	900 VDC
Temperature Range	-40/+105°C
Rated Temperature	85°C
Dissipation Factor	0.02%
Insulation Resistance	1.5 GOhms
Max dV/dt	16 V/us
Resistance	3.9 mOhms (10kHz 70C)
Ripple Current	15 Amps (10kHz 70C), 321 Amps (Peak)

Dimensions	
L	42mm MAX
H	45mm MAX
T	30mm MAX
S	37.5mm MAX
S1	10.16mm MAX
LL	6mm -2mm

Packaging Specifications	
Packaging	Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.