

## LED enclosure light - PLD E 409 W 350 MS - 1319573

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



LED enclosure light, color temperature 5000 K, length 350 mm, Housing: Polycarbonate, can be swiveled, can be switched in series, with motion detector, including mounting accessories

### Product Description

The LED light is designed to illuminate the interior of control cabinets.  
The prismatic integrated into the light cover ensures optimum illumination of the control cabinet.  
You can use magnets or screws to affix the light holder.  
The light can swivel in the holder.  
Connect the supply voltage to the light via Push-in connection. You do not require special connectors for this.  
You can connect several lights in succession.  
A button is used to switch the light on and off.

### Your advantages

- ✓ Series connection reduces cabling effort for control cabinets arranged in series
- ✓ Optimum lighting of the control cabinet, thanks to integrated prismatic and capacity to swivel
- ✓ Swiveling enables optimum adjustment to the relevant control cabinet depth
- ✓ LED service life of 50,000 h (L70 value) prevents bulb replacement



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 604172
GTIN	4063151604172
Custom tariff number	94054039
Country of origin	Germany

### Technical data

#### Dimensions

# LED enclosure light - PLD E 409 W 350 MS - 1319573

## Technical data

### Dimensions

Width	30 mm
Height	40 mm
Length	350 mm

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 90 %
Permissible humidity (storage/transport)	5 % ... 90 %
Degree of protection	IP20

### General

Socket	none
Color	traffic grey A RAL 7042
Net weight	150 g
Mounting type	Screw mounting
	Magnet mounting
Mounting position	any

### Power supply for module electronics

Connection method	Push-in connection
Number of positions	2
Supply voltage range	24 V AC/DC ... 240 V AC/DC (50/60 Hz (AC))
Power consumption	6 W

### Connection data

Connection method	Push-in connection
Conductor cross section solid min.	0.13 mm <sup>2</sup>
Conductor cross section solid max.	1.5 mm <sup>2</sup>
Conductor cross section flexible min.	0.13 mm <sup>2</sup>
Conductor cross section flexible max.	1.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	16
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.5 mm <sup>2</sup> ... 0.75 mm <sup>2</sup> (DIN 46228-4)
Conductor cross section flexible, with ferrule without plastic sleeve	0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (DIN 46228-1)
Stripping length	10 mm

### Light properties

Source of light type	LED
Number of LEDs	18

# LED enclosure light - PLD E 409 W 350 MS - 1319573

## Technical data

### Light properties

Service life, lighting appliance	50000 h
Light color	Neutral white
Color temperature / wavelength	5000 K
Color rendering index	85
Luminous flux	700 lm (Net luminous flux)
Illumination	max. 1200 lx (50 cm distance)
Energy efficiency class	Delegated Regulation (EU) 2019/2015
	This product contains an energy efficiency class D light source.
	D (1 light source)

### Motion detector

Detection range	max. 5 m
Detection angle	100 °
Lighting duration	5 min. (Retriggered)


### Standards and Regulations

Immunity to ESD	Immunity test in accordance with EN 61000-6-2/IEC 61000-6-2 Electrostatic discharge (ESD) EN 61000-4-2/IEC 61000-4-2 Criterion A, 4 kV contact discharge, 8 kV air discharge
Immunity to EF	Immunity test in accordance with EN 61000-6-2/IEC 61000-6-2 Electromagnetic fields EN 61000-4-3/IEC 61000-4-3 Criterion A, Field intensity: 10 V/m
Immunity to burst	Immunity test in accordance with EN 61000-6-2/IEC 61000-6-2 Fast transients (burst) EN 61000-4-4/IEC 61000-4-4 Criterion A, ±2 kV
Immunity to surge	Immunity test in accordance with EN 61000-6-2/IEC 61000-6-2 Transient overvoltage (surge) EN 61000-4-5/IEC 61000-4-5 Criterion A, ±1 kV
Immunity to conducted interference	Immunity test in accordance with EN 61000-6-2/IEC 61000-6-2 Conducted interference EN 61000-4-6/IEC 61000-4-6 Criterion A, Test voltage 10 V
Interference emission	Noise emission test in accordance with EN 55015/IEC 55015
Mechanical tests	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6 5g
	Shock in acc. with EN 60068-2-27/IEC 60068-2-27 25g
	Continuous shock according to EN 60068-2-27/IEC 60068-2-27 10g
Protection class	II

## Drawings

# LED enclosure light - PLD E 409 W 350 MS - 1319573

Dimensional drawing




Schematic diagram



Connection of a light

Schematic diagram



Series connection of two lights

## Classifications

eCl@ss

eCl@ss 10.0.1	27182808
eCl@ss 11.0	27182808
eCl@ss 9.0	27189241

## Approvals

Approvals

Approvals


UL Recognized / cUL Recognized / cULus Recognized


Ex Approvals

Approval details

# LED enclosure light - PLD E 409 W 350 MS - 1319573

## Approvals

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 255026
mm <sup>2</sup> /AWG/kcmil	30-14		

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 255026
mm <sup>2</sup> /AWG/kcmil	30-14		

cULus Recognized			
------------------	---	--	--