

Specification Sheet

Part Number: 323-50013



Article Number

323-50013

Type

TREDUX MA47-48ST-40/12

Color

Black (BK)

Features & Benefits

- Medium wall tubing resists solvents, acids and alkaline solutions while providing good mechanical strength.
- Features robust insulation characteristics designed for low voltage power applications.
- Adhesive lining provides excellent insulation against moisture and humidity.
- RoHS compliant and Halogen-free.

Quantity Per

pcs.

Product Description

MA47 is a medium wall heat shrink tubing with an adhesive lining for use in low voltage applications. The thermoplastic adhesive liner provides excellent moisture sealing and insulation protection of cable joints and terminations. Made of a polyolefin outer material, this tubing has a shrink ratio up to 4 to 1. The adhesive lining begins to activate as the temperature approaches 185° F (85° C). Individually labeled 4-foot sticks come packaged in a retail display box.

Short Description

Heat Shrink Tubing, 4' Long Stick, Medium Wall Adhesive Lined, Upt 4:1, 1.5", 40/12 dia, PO, Black, 4/pkg

Global Part Name

TREDUX MA47-48ST-40/12-PO-X-BK

Length L (Imperial)

4.0

Length L (Metric)

1.0

Voltage Range

Low and medium voltage

Variant

Medium-Wall

Nominal Diameter (Imperial)

1-1/2

Nominal Diameter (Metric)

40

Wall Thickness WT (Imperial)

.09

Wall Thickness WT (Metric)

2.5

Material

Polyolefin, cross-linked (PO-X)

Material Shortcut

PO-X

Adhesive

Hot melt adhesive

Flammability

Not Flame Retardant

Halogen free

Yes

Operating Temperature (Metric) -67°F to +230°F (-55°C to +110°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 2

Package Quantity (Metric) 2

Customs Number 3926909987

Weight (Metric) 0.94

Weight (Imperial) 2.08