



**Metric table**

Dimensions in: millimeters - inches

<b>1</b> d <sub>1</sub>	<b>2</b> d <sub>2</sub> Thread	<b>3</b> Length l				d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	S
34 1.34	M 6	15 .59	20 .79	25 .98	30 1.18	17 .67	22 .87	20 .79	12 .47	7 .28
34 1.34	M 8	15 .59	20 .79	25 .98	-	17 .67	22 .87	20 .79	12 .47	7 .28
45 1.77	M 8	20 .79	30 1.18	40 1.57	-	25 .98	30 1.18	27 1.06	18 .71	85 3.35
45 1.77	M 10	30 1.18	-	-	-	25 .98	30 1.18	27 1.06	18 .71	85 3.35
65 2.56	M 10	30 1.18	-	-	-	30 1.18	39 1.54	36 1.42	25 .98	10 .39

**Specification**

- Three-lobed knob  
Phenolic plastic
  - Temperature resistant up to 300 °F (150 °C)
  - Black, shiny finish
- Threaded stud  
Steel
  - Zinc plated
  - Molded-in
- RoHS compliant

**Information**

3P-P three-lobed knobs have an aesthetically pleasing shape, provide a comfortable grip and expand the range of clamping options.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- *Three-Lobed Knobs 3P-B (with Brass Tapped Insert)*

How to order	1
<b>1</b> Handle diameter d <sub>1</sub>	
<b>2</b> Thread d <sub>2</sub>	
<b>3</b> Length l	

**3P-P-45-M8-30**