



Click [here](#) for the 3D model.

Dimensions	
D	85mm +2mm
L	144.5mm +/-2mm
L1	146mm +/-2mm
S	32mm +/-0.3mm
D1	88mm +0.5mm

Packaging Specifications	
Mounting	Bolt - M12x16
Packaging	Bulk, Bag
Packaging Quantity	5

General Information	
Series	C44U-M
Dielectric	Metallized Polypropylene
Style	Can
Features	DC Filtering, Energy Storage
RoHS	With Exemptions
REACH	SVHC (Pb - CAS 7439-92-1)
SCIP Number	cc1c1ec4-db9e-4815-b26b-e8a34ddfb776
Lead	Screw Terminals M6
AEC-Q200	No
Component Weight	1120 g
Miscellaneous	Thermal Resistance = 5.1 C/W. Weight = 5600 grams.

Specifications	
Capacitance	600 uF
Capacitance Tolerance	10%
Voltage DC	900 VDC
Temperature Range	-40/+85°C
Rated Temperature	75°C
Insulation Resistance	50 MOhms
Max dV/dt	6 V/us
Resistance	2.4 mOhms (10kHz)
Ripple Current	49 Amps (10kHz 40C), 3505 Amps (Peak)
Inductance	55 nH