

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	16APR2015	DW	CW
	B	ECR-15-018270	09DEC2015	DW	CW
	C	ECR-21-111798	27SEP2021	WQR	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 830V  
RATED CURRENT: 16A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 8KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40\sim+125^{\circ}C$   
WIRE RANGE:  $0.14\sim 4\text{ mm}^2$  (26~12 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING:T20300X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 830V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 8KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40\sim+125^{\circ}C$   
接线范围:  $0.14\sim 4\text{ mm}^2$  (26~12 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20300X10XX000)

HMN-006-PM	T2111063101-000
DESCRIPTION	PART NUMBER

TE Connectivity

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	16APR2015	NAME	HMN-006-PM
		CHK	16APR2015		
		APVD	16APR2015		
		PRODUCT SPEC	108-137120		
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	114-137120
		0 PLC	±-	SIZE	A3
		1 PLC	±-	CAGE CODE	00779
		2 PLC	±-	DRAWING NO	T2111063101000
		3 PLC	±-	RESTRICTED TO	-
		4 PLC	±-	SCALE	3:2
		ANGLES	±-	SHEET	1 OF 1
MATERIAL		FINISH	-	REV	C
			-	Customer Drawing	

1470-19 (3/13)