ABSOCIATION CONNECTING ELECTRONICE INDUSTRIES® INCLUSTRIES® INCLUSTRIES®	ourn, Illinois, All rights reserved u	under both level	document i parts, the c	is a declaratio leclaration en	n of the substa compasses all	ances wit l lower le	thin the manufacture wel materials for wh	er listed ite nich the m	em. Note: if anufacturer h	the item is an as as engineering	sembly with lower responsibility.	
2-21.1 IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and				als and Mf	and Mfg Information				
Supplier Information												
Company name*		Unique ID Authority				Response Date*						
onsemi									2023-06-08			
Contact Name	Title - Contact		Pho	Phone - Contact*				Email - Contact*				
Product-Env-Stewards	Product Enviro Compliance		NA	NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*		Phone - Representative*				Email - Representative*						
Product-Env-Stewards		NA				Product-Env-Stewards@onsemi.com						
Requester Item Number Mfr Item	Number Mfr Item Name	Mfr Item Name		fective Date	Version	Mar	Manufacturing Site		Veight*	UOM	Unit Type	
NLV74H G	IC4051ADR2 ANALOG MUL	TIPLEXERS/DEMUL	. 20	23-06-08		PH1		1	42.68	mg	Each	
Manufacturing Proccess Information												
Terminal Plating / Grid Array Material	Ferminal Base Alloy J-STD-020 MS		ng	Peak Proces	k Process Body Temperature Max Time at		Max Time at Peak	k Temperature Number of Reflow Cycles		les		
Matte Tin (Sn) - annealed CU Alloy 1		1		260	С		30	second	ls 3			
Comments												
level 1 - maximum time at peak temperature during so	dering is 10-30 seconds											
For more information regarding material composition	0											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the				
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg
Die Attach	4.85	mg		Epoxy resin	proprietary data		0.485	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.2425	mg
			Supplier	Silver (Ag)	7440-22-4		3.88	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.2425	mg
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg
			Supplier	Copper (Cu)	7440-50-8		73.035	mg
Mold Compound-Black	55.11	mg		Epoxy resin	proprietary data		2.7555	mg
			Supplier	Phenolic Resin	Proprietary Data		2.7555	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.1022	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2756	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		48.2213	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Cu	0.34	mg	Supplier	Copper (Cu)	7440-50-8		0.34	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).