	I	വ	ات		m	D	0	D. D	Þ		٦
		V Thread	ØS								4
ω							LAYOUT SHO	OWN AS EXAMPLE			3
			Keying	Shown as example							
CHARACTE	RISTICS			Conne	ector dimension						
-Standard : I	ased on MIL-DTL-38	99 Series III		Dim	Nominal						
-Shell Plating -Insulator -Contacts	-Insulator : Thermoplastic -Contacts : Copper Alloy					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Seals & Gro ► -Contact Pla			nimum						tion & Control List Not Listed		2
-Durability							PN: 8D511W22PN				
-Temperatur	-					A 18-10	0-2016 First Release				
-Salt Spray ————————————————————————————————————	: 500 hoi : 14.47 g					ISS DA Designed By:	ATE Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	
						TITLE	E .	Aluminium Plug 8D	series		
BASIC SERIES	: : Plug with RFI Shield		11 W 22 P	N		SCALE NA		ral linear rances: ±	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : N				SOURIAU This document is the propusition SOURIAU SOURIAU it must not be reproduced			ed or			
SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)				FORMAT	communicated without permis						
PLATING :	W = Olive drab	Cadmium			CONTACT LAYOUT : 11-22	A3		JRIAU DRG N° 511W22PN-C		SHEET 1/2	
									I	1/1	

		۵	н т	m		0	
4		Contact Layout 22*					
 دى	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	oducts w
N						PN: 80	Coun FR 0511
_					A 18-10-2016 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
-					SCALE NA SOURIAU	Gener Tole	Alumi ral linear erances: ±
					FORMAT		JRIAU

G

Н

F

Е

A3

D

С

