


SBCP-87HY330H

Aliases (UPIO87HY330H00) KEMET, SBCP-87HY, Power, 33 uH, 20%, 5mm



Click here for the 3D model.

Dimensions	
D	9.5mm MAX
L	8.5mm MAX
S	5mm +/-0.5mm
LL	3.5mm +1/-0.5mm
F	0.6mm NOM

Dackaging	Chacifications
Гаскачну	Specifications

Component Weight	1.6 g
Packaging	Ammo
Packaging Quantity	2000

General Information		
Series	SBCP-87HY	
Style	Through-Hole	
Description	Radial Leaded, Ferrite Power Inductors	
Features	DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core	
RoHS	Yes	
Lead	Wire Leads	
Core	Ferrite	
Notes	Contains 4 Reels of 500 pieces each.	

Specifications				
Inductance	33 uH			
Inductance Tolerance	20%			
Temperature Range	-20/+105°C			
Shielded	No			
Current	1.5 Amps			
DC Resistance	0.12 Ohms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.