

Electronic housing - ME MAX 45 MT 3-3 KMGY - 2890975

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Intermediate element, Central part, width: 22.6 mm, color: light gray (7035)

Your advantages

- Item is from the ME-MAX product range
- Easy mounting
- Available in overall widths from 6.2 mm to 90 mm, modular extension is possible
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting as well as power connection system



Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 106399
GTIN	4046356106399

Technical data

Item properties

Brief article description	Electronic housing
Type	ME MAX 45 MT 3-3 KMGY
Order No.	2890975
Housing type	Intermediate element
Type	Central part

Dimensions

Width [w]	22.6 mm
Height [h]	99 mm
Depth [d]	112.5 mm
Depth from top edge of DIN rail [d]	107 mm

Material data

Flammability rating according to UL 94	V0
Housing material	Polyamide

Ambient conditions

Electronic housing - ME MAX 45 MT 3-3 KMGY - 2890975

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Packaging information

Pieces per package	10
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals


Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	---	---	---------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>