



AUDIO  
TECHNOLOGIES®

## XLR CHASSIS CONNECTORS

### 4 PIN E SERIES - VERTICAL PCB MOUNT

Locking vertical PCB mount 4 pin chassis connector with plastic body perfect for use in DC power, aviation, communications, and other AV applications.

Other Available Mounting Option: Horizontal



IO-XLR4-M-EV

IO-XLR4-F-EV

## SPECIFICATIONS

### PRODUCT

Gender: **Male (IO-XLR4-M-EV)**

**Female (IO-XLR4-F-EV)**

Contacts: **4**

### ELECTRICAL

Capacitance Between Contacts: **≤ 3.4 pF**

Capacitance Between Contact and Ground: **≤ 3.2 pF**

Contact Resistance: **< 6 mΩ**

Insulation Resistance: **≥ 5000 MΩ**

Dielectric Strength: **1500V @ 60s**

Current Rating: **3A / 50V AC**

Grounding: **Separate ground terminal. Grounds to shell of mating connector and panel**

### ENVIRONMENTAL

Standard Compliance: **IEC 61076-2-103**

UL Flammability Rating: **UL94 V-0**

Temperature Range: **-40°C ~ +70° C (-40°F ~ +158°F)**

### MECHANICAL

Lifetime: **> 1000 Mating Cycles**

Wiring: **Vertical PCB Mount**

Locking Device: **Latch Lock**

Mounting Direction: **Rear**

Solderability: **Complies with IEC 60068-2-20**

### MATERIAL

Contacts: **Gold Plated Brass**

Ground Terminal: **Nickel Plated Brass**

Shell: **Polyamide**

Shell Finish: **Black**

Push Button: **Nickel Plated Brass**


Latch: **Nickel Plated Carbon Steel**

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.  
10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 |  
www.ioaudiotechnologies.com



## Panel Cutout



## FEATURES & APPLICATIONS

E Series XLR chassis connectors offer the most cost-effective solution for design-in applications where the termination method is to a printed circuit board. The small footprint makes this our XLR receptacle with the highest packing density available. These connectors feature a compact all plastic housing with precision machined, one piece, gold plated contacts to help prolong the useful life of the connectors. They also come with a separate nickel plated ground pin that grounds the connector to the panel. The compact form factor of these connectors makes them perfect for situations where space saving is a priority or space for a connector is limited.

Available in 3, 4, or 5 pin, Male or Female variations with options for vertical or horizontal PCB mounting.

### PART NUMBER BREAKDOWN:

IO-**XLR**4-M-EV  
Series Identifier  
IO-**XLR**4-M-EV  
Number of Pins  
IO-**XLR**4-**M**-EV  
Gender  
IO-**XLR**4-M-**EV**  
Series Identifier  
IO-**XLR**4-M-**EV**  
H = Horizontal PCB Mount  
V = Vertical PCB Mount

### STANDARDS & CLASSIFICATIONS



Product specifications may change without prior notification