




| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 37.4 |
| B | 1 1/4-18NEF-2B |
| C1 | 15.9 |
| C2 | - |
| D | 68 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|-------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3 | DICKTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 5 | KONTAKTSTIFT / CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 12 | ENDGEHÄUSE / ENDBELL |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|--------------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Zinc cobalt, black |
| Insulator Material: | Neoprene |
| Contact Material: | Copper alloy |
| Contact Plating: | Gold 0,5 & #956; |

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



description CA3106E20-27P-A176-A232
Plug, straight
Endbell with clamp and bushing
Solder Cup / Pin / Layout: 20-27

© All rights reserved. Reproduction or issue to third in any form
whenever is only permitted with written authorization of ITT Cannon



page 1/1
revision 929 11. Jun 19