

## Specification Sheet

Part Number: T50MI0M4



1-Piece Cable Tie/Screw Mount, 12.4" Long, #10 Screw, 3.4" Max Bundle Dia, 50lb, PA66, Black, 1000/pkg

Article Number	113-00031
Type	T50MI
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Mount design secures firmly with any #10 screw.</li><li>• Screw mount style creates low insertion and high extraction force.</li></ul>
Quantity Per	bag
Product Description	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
Short Description	1-Piece Cable Tie/Screw Mount, 12.4" Long, #10 Screw, 3.4" Max Bundle Dia, 50lb, PA66, Black, 1000/pkg
Global Part Name	T50MI-PA66-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225
<b>Length L (Imperial)</b>	12.4
<b>Length L (Metric)</b>	315.0
<b>Fixation Method</b>	Fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.7
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	3.4
<b>Bundle Diameter Max (Metric)</b>	85.0
<b>Height H (Imperial)</b>	.23
<b>Height H (Metric)</b>	5.70

**Mounting Hole Diameter D (Imperial)** 0.22

**Mounting Hole Diameter D (Metric)** 5.5 mm

**Mounting Hole Diameter D Max (Metric)** 5.5

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**ROHS Complaint** Yes

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988

