



HARTING PushPull, type acc. to IEC 61 076-3-106 variant 4  
cable to cable housing

### Features

- HARTING PushPull technology
- Ideal for prototyping
- Can be combined with panel feed-throughs for power, data and signal

### Technical characteristics

Locking	PushPull technology acc. to IEC 61076-3-106 variant 4
Degree of protection	IP65 / IP67
Outer cable diameter	6.5 ... 9.5 mm
Mating cycles	min. 750
Temperature range	-40 °C ... +70 °C
Housing material	Plastic, black
Flammability acc. to UL 94	V0

Identification	Part number	Drawing	Dimensions in mm
<b>HARTING PushPull cable to cable housings, plastic</b> (Order housing bulkhead mounting and insert separately)  for outer cable diameter 6.5 ... 9.5 mm	09 45 345 0000	2X M2.5x10 self tapping screws according to EN ISO 7092 	
<b>HARTING PushPull bulkhead housings, plastic</b> (Order housing bulkhead mounting and insert separately)	09 45 345 0001	2X M2.5x10 self tapping screws according to EN ISO 7092 	
<b>Suitable bulkhead housing, plastic</b>  for RJ45 / Signal	09 45 545 0028		
<b>Inserts for RJ45 / Signal</b> RJ 45: 8-poles, Cat. 6 / class E <sub>A</sub> Ha-Vis preLink® set AWG 22/23 HARTING RJ Industrial® cable jack with IDC termination AWG 22-24, 8-poles AWG 24-28, 8-poles AWG 22-24, 4-poles, Cat. 5	20 82 001 0001  09 45 545 1562 09 45 545 1561 09 45 545 1120		
Signal: 10-poles, 50 V / 5 A*	09 45 545 9010		

\* Order D-Sub crimp male contacts separately (see pages 02.19 and 02.20)