

841WB

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 841WB**Other Means of Identification:** Super Shield™ Water Based Nickel Conductive Paint /
Peinture de Nickel Conducteur Super Shield™ à Base d'Eau**Related Part #** 841WB-15ML, 841WB-150ML, 841WB-850ML, 841WB-3.78L

Recommended Use and Restriction on Use

Use: Nickel filled, electrically conductive coating**Uses Advised Against:** Not for sale in the EU.

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

+1-800-340-0772

FAX +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)



For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

841WB
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Reproductive Toxicity	1	Danger	Health
Specific Target Organ Toxicity Repeated Exposure	1	Danger	Health
Carcinogenicity	2	Warning	Health
Sensitization Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment Chronic	3	<i>none</i>	<i>none</i>

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H360: May damage fertility or the unborn child H372: Causes damages to organs (lungs) through prolonged or repeated exposure by inhalation H351: Suspected of causing cancer
	H317: May cause allergic skin reaction
<i>None</i>	H412: Harmful to aquatic life with long lasting effects

Section continued on the next page

841WB
Continued ...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist, spray, and vapors.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing, and eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
Response	Precautionary Statements
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P314	Get medical attention or advice if you feel unwell.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

841WB
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-02-0	nickel	48%
872-50-4	1-methyl-2-pyrrolidone	4%
14807-96-6	talc	1%
121-44-8	triethylamine	0.4%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364, P308 + P313
Immediate Symptoms	<i>dry skin, redness, allergic rash</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice or attention.
IF INHALED	P304 + P340, P308 + P313
Immediate Symptoms	<i>cough, shortness of breath, headache</i>
Response	Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice or attention.
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	<i>redness, blurred vision, pain</i>
Response	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED	P301 + P330 + P331, P308 + P313
Immediate Symptoms	<i>low toxicity: no symptoms known or expected</i>
Response	Rinse mouth. Do NOT induce vomiting. IF exposed or concerned: Get medical advice or attention.

841WB

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire use extinguishing media suitable for surrounding material.
Specific Hazards	Produces irritating and toxic fumes in fires or in contact with hot surfaces. May produce very toxic nickel carbonyl gas in the presence of carbon monoxide in a reducing atmosphere.
Combustion Products	Produces carbon oxides (CO, CO ₂), nickel oxides fumes, and nitrogen oxides (NO _x).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommendations in Section 8.
Precautions for Response	Do not breathe the mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, waste container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

841WB
Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Do not breathe mist, spray, and vapors. Do not eat, drink, or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Handling

Wear protective gloves, protective clothing, and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment.

Storage

Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
nickel	ACGIH	1.5 mg/m ³	Not established
	U.S.A. OSHA PEL	1 mg/m ³	Not established
	Canada AB	1.5 mg/m ³	Not established
	Canada BC	0.05 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	1 mg/m ³	Not established
talc (non-asbestos fiber)	ACGIH	2 mg/m ³	Not established
	U.S.A. OSHA PEL	20 mppcf ^{a)}	Not established
	Canada AB	2 mg/m ³	Not established
	Canada BC	2 mg/m ³	Not established
	Canada ON	2 mg/m ³	Not established
	Canada QC	3 mg/m ³	Not established

Section continued on the next page

841WB
Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
triethylamine	ACGIH	100 mg/m ³	12 mg/m ³
	U.S.A. OSHA PEL	15 ppm	Not established
	Canada AB	1 ppm	3 ppm
	Canada BC	1 ppm	3 ppm
	Canada ON	0.5 ppm	1 ppm
	Canada QC	10 ppm	15 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

- a) Million particles per cubic foot of air, based on impinge samples counted by light-field technique.

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely or incidental contacts, use nitrile, neoprene, or other chemically resistant gloves.

Section continued on the next page

841WB

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges and particulate filter.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not applicable
Appearance	Dark grey	Upper Flammability Limit	Not applicable
Odor	Musty	Vapor Pressure ^{a)}	23 hPa [17 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.82
Freezing/Melting Point	Not available	Solubility in Water	Miscible
Initial Boiling Point	100 °C [212 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point	Not available	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @40 °C	Not available

a) Calculated using from volatile components parameters and Raoult's Law.

841WB

Section 10: Stability and Reactivity

Reactivity	The nickel can react vigorously with acids and liberate hydrogen, which can form an explosive mixture in air. Nickel may react with carbon monoxide in a reducing atmosphere to form a very toxic nickel carbonyl gas.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, excessive heat, and incompatible substances
Incompatibilities	Oxidizing agents, strong acids, acid anhydrides
Polymerization	Will not occur
Decomposition	Does not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	May cause redness, blurred vision and pain.
Skin	May cause dry skin, redness and allergic rash.
Inhalation	May cause cough, shortness of breath and headaches.
Ingestion	Low toxicity: no symptoms known or expected.
Chronic	Chronic inhalation exposure to nickel dust, mist, or spray may affect the central nervous system, damage lungs. Nickel is suspected of being a carcinogen.

Section continued on the next page

841WB
Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
nickel	9 000 mg/kg Rat	Not available	10.2 mg/L 1 h Rat
1-methyl-2-pyrrolidone	3 914 mg/kg Rat	8 000 mg/kg Rabbit	>5.1 mg/L Rat 4 h (mist)
talc	Not available	Not available	Not available
triethylamine	730 mg/kg Rat	580 mg/kg Rat	3 496 ppm 1 hr Rat
ATE Mixture	>2 000 mg/kg	>2 000 mg/kg	>100 mg/L

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects
Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met. Contains mechanically abrasive particles.

Sensitization
 (allergic reactions)

Exposure to nickel may cause allergic skin reaction.

Carcinogenicity
 (risk of cancer)

Nickel is classified as a suspect carcinogen based on animal intratracheal instillation (intubation) or interperitoneal (in body cavity) injection studies. A reliable 2008 study by Oller et al. shows no carcinogenicity for the nickel metal via normal inhalation route.

Nickel [7440-02-0]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A5: Not suspected as a human carcinogen

CA Prop 65: Listed as a carcinogen

NTP: Reasonably anticipated to be human carcinogen

Section continued on the next page

841WB

Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	At large doses of >4 000 mg/kg, 1-methyl-2-pyrrolidone shows reproductive effects based on studies in rats and mice. 1-methyl-2-pyrrolidinone [CAS# 872-50-4] CA Prop 65: Listed as a reproductive toxicant
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Nickel particles can damage the respiratory tract leading to inflammation, lung fibrosis, and accumulation of nickel particles in a rat study.
Aspiration hazard	There are no category 1 components, and the kinematic viscosity of the mixture is >20.5 mm ² /s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Nickel powder less than 1 mm diameter is classified as a chronic category 3 aquatic pollutant by ECHA registrants.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

Biodegradability

The nickel content is not biodegradable.

Section continued on the next page

841WB**Other Effects**

Actual VOC = 5.1% [28 g/L]; Regulated VOC = 477 g/L

Note: Nickel can be recovered from the waste to reclaim the value of the nickel.

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground**

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations) and **US DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to IMDG Dangerous Goods Regulations.

Not Regulated

841WB

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	0
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains nickel (CAS# 7440-02-0, reportable quantity = 100 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

841WB**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA)

This product contains nickel, which is listed as a carcinogen. This product contains 1-methyl-2-pyrrolidinone (CAS# 872-50-4), which is listed as reproductive toxicity.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemicals' Regulatory Department

Date of Review 08 April 2022

Supersedes 27 February 2020

Reason for Changes: New formulation

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

841WB**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario,
Canada
L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.