



LED Display Product Data Sheet LTC-5851Y

Spec No.: DS30-2002-034

Effective Date: 06/18/2002

Revision: -

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

FEATURES

- * 0.56 inch (14.22 mm) DIGIT HEIGHT.
- * CONTINUOUS UNIFORM SEGMENTS.
- * LOW POWER REQUIREMENT.
- * EXCELLENT CHARACTERS APPEARANCE.
- * HIGH BRIGHTNESS & HIGH CONTRAST.
- * WIDE VIEWING ANGLE.
- * SOLID STATE RELIABILITY.
- * CATEGORIZED FOR LUMINOUS INTENSITY.

DESCRIPTION

The LTC-5851Y is a 0.56 inch (14.22 mm) digit height quadruple digit seven-segment display. This device utilizes Yellow LED chips, which are made from GaAsP on GaP substrate, and has light gray face and white segments.

DEVICE

PART NO.	DESCRIPTION
Yellow	Common Anode
LTC-5851Y	

PIN CONNECTION

NO.	CONNECTION	NO.	CONNECTION
1	CATHODE E (DIGIT 1)	19	CATHODE B (DIGIT 4)
2	CATHODE D (DIGIT 1)	20	CATHODE A (DIGIT 4)
3	CATHODE C (DIGIT 1)	21	CATHODE F (DIGIT 4)
4	CATHODE DP (DIGIT 1)	22	CATHODE DP (DIGIT 4)
5	CATHODE E (DIGIT 2)	23	CATHODE B (DIGIT 3)
6	CATHODE D (DIGIT 2)	24	CATHODE A (DIGIT 3)
7	CATHODE G (DIGIT 2)	25	CATHODE G (DIGIT 3)
8	CATHODE C (DIGIT 2)	26	CATHODE F (DIGIT 3)
9	CATHODE DP (DIGIT 2)	27	CATHODE DP (DIGIT 3)
10	CATHODE E (DIGIT 3)	28	CATHODE B (DIGIT 2)
11	CATHODE D (DIGIT 3)	29	CATHODE A (DIGIT 2)
12	CATHODE C (DIGIT 3)	30	CATHODE F (DIGIT 2)
13	COMMON ANODE (DIGIT 3)	31	COMMON ANODE (DIGIT 2)
14	COMMON ANODE (DIGIT 4)	32	COMMON ANODE (DIGIT 1)
15	CATHODE E (DIGIT 4)	33	CATHODE B (DIGIT 1)
16	CATHODE D (DIGIT 4)	34	CATHODE A (DIGIT 1)
17	CATHODE G (DIGIT 4)	35	CATHODE G (DIGIT 1)
18	CATHODE C (DIGIT 4)	36	CATHODE F (DIGIT 1)

ABSOLUTE MAXIMUM RATING AT Ta=25°C

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation Per Segment	60	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	80	mA
Continuous Forward Current Per Segment	20	mA
Derating Linear From 25°C Per Segment	0.27	mA/°C
Reverse Voltage Per Segment	5	V
Operating Temperature Range	-35°C to +85°C	
Storage Temperature Range	-35°C to +85°C	
Solder Temperature: max 260°C for max 3sec at 1.6mm[1/16inch] below seating plane.		

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I _v	800	2400		μcd	I _F =10mA
Peak Emission Wavelength	λ _p		585		nm	I _F =20mA
Spectral Line Half-Width	Δλ		35		nm	I _F =20mA
Dominant Wavelength	λ _d		588		nm	I _F =20mA
Forward Voltage Per Segment	V _F		2.1	2.6	V	I _F =20mA
Reverse Current Per Segment	I _R			100	μA	V _R =5V
Luminous Intensity Matching Ratio	I _v -m			2:1		I _F =10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.1. RELATIVE INTENSITY VS. WAVELENGTH




Fig.2. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT (REFRESH RATE 1KHz)




Fig.3. FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5. MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE.




Fig.6. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)