



LASER MARKING DETAILS	
R25 X YR/WK	
B VALUE	CODE(X)
3982	MD

RESISTANCE VS TEMP CHARACTERISTICS:

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	293.5	306.8	320.7	50	3.485	3.556	3.629
-35	214.7	223.8	233.1	55	2.874	2.939	3.005
-30	158.8	165.0	171.3	60	2.382	2.441	2.500
-25	118.6	122.8	127.2	65	1.984	2.036	2.090
-20	89.390	92.320	95.340	70	1.660	1.706	1.754
-15	68.150	70.190	72.290	75	1.394	1.436	1.479
-10	52.350	53.780	55.230	80	1.176	1.213	1.251
-5	40.500	41.500	42.510	85	0.997	1.030	1.065
0	31.550	32.250	32.950	90	0.849	0.879	0.909
5	24.710	25.190	25.680	95	0.725	0.752	0.779
10	19.480	19.810	20.150	100	0.622	0.646	0.670
15	15.450	15.680	15.910	105	0.535	0.557	0.579
20	12.330	12.490	12.640	110	0.462	0.481	0.501
25	9.900	10.000	10.100	115	0.401	0.418	0.436
30	7.954	8.052	8.150	120	0.348	0.364	0.380
35	6.425	6.517	6.611	125	0.303	0.317	0.332
40	5.215	5.301	5.388	130	0.258	0.270	0.284
45	4.253	4.332	4.412	135	0.213	0.223	0.236

NOTES:

- RESISTANCE TOLERANCE @ 25°C : 10KΩ±1%.
- B-VALUE(25/85°C) : 3982K±1%.
- OPERATING TEMPERATURE RANGE : -40°C TO +105°C.
- RING TERMINAL MOUNTING HOLE DIAMETER : 3.7MM.
- TERMINAL IS NICKEL PLATED COPPER.
- VOLTAGE BREAKDOWN STRENGTH : MIN 1500VAC FOR 3SEC BETWEEN CONDUCTOR AND EYELET/RING LUG
- RESPONCE TIME : APPROX 10 SECOND IN LIQUID MEDIUM
- INSULATION RESISTANCE :MINIMUM OF 100MOHM @ 500VOLTS DC IN METALIC BALLS.

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	CURRENT REV DESC:																																				
	<table border="1"> <tr> <th>DIMENSION UNITS</th> <th>SCALE</th> </tr> <tr> <td>mm</td> <td>NTS</td> </tr> </table>	DIMENSION UNITS	SCALE				mm	NTS	<table border="1"> <tr> <th colspan="3">GENERAL TOLERANCES (UNLESS SPECIFIED)</th> </tr> <tr> <td>ANGULAR TOL</td> <td>±</td> <td>'</td> </tr> <tr> <td>4 PLACES</td> <td>±</td> <td></td> </tr> <tr> <td>3 PLACES</td> <td>±</td> <td></td> </tr> <tr> <td>2 PLACES</td> <td>±</td> <td></td> </tr> <tr> <td>1 PLACE</td> <td>±</td> <td></td> </tr> <tr> <td>0 PLACES</td> <td>±</td> <td></td> </tr> </table>		GENERAL TOLERANCES (UNLESS SPECIFIED)			ANGULAR TOL	±	'	4 PLACES	±		3 PLACES	±		2 PLACES	±		1 PLACE	±		0 PLACES	±		<table border="1"> <tr> <td>EC NO: 657688</td> <td>2021/03/09</td> </tr> <tr> <td>DRWN: RAVIKM</td> <td>2021/03/17</td> </tr> <tr> <td>CHK'D: RBBHASKAR</td> <td>2021/03/17</td> </tr> <tr> <td>APPR: RBBHASKAR</td> <td>2021/03/17</td> </tr> </table>			EC NO: 657688	2021/03/09	DRWN: RAVIKM	2021/03/17
DIMENSION UNITS	SCALE																																					
mm	NTS																																					
GENERAL TOLERANCES (UNLESS SPECIFIED)																																						
ANGULAR TOL	±	'																																				
4 PLACES	±																																					
3 PLACES	±																																					
2 PLACES	±																																					
1 PLACE	±																																					
0 PLACES	±																																					
EC NO: 657688	2021/03/09																																					
DRWN: RAVIKM	2021/03/17																																					
CHK'D: RBBHASKAR	2021/03/17																																					
APPR: RBBHASKAR	2021/03/17																																					
DIVISIONAL SYMBOLS	<table border="1"> <tr> <th colspan="3">INITIAL REVISION:</th> </tr> <tr> <td>DRWN: RAVIKM</td> <td>2021/03/09</td> <td></td> </tr> <tr> <td>APPR: RBBHASKAR</td> <td>2021/03/17</td> <td></td> </tr> </table>	INITIAL REVISION:			DRWN: RAVIKM	2021/03/09		APPR: RBBHASKAR	2021/03/17		<table border="1"> <tr> <th>DOCUMENT NUMBER</th> <th>DOC TYPE</th> <th>DOC PART</th> <th>REVISION</th> </tr> <tr> <td>2138651633</td> <td>PSD</td> <td>000</td> <td>A</td> </tr> </table>		DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION	2138651633	PSD	000	A	<table border="1"> <tr> <th>MATERIAL NUMBER</th> <th>CUSTOMER</th> <th>SHEET NUMBER</th> </tr> <tr> <td>2138651633</td> <td>OTS</td> <td>1 OF 1</td> </tr> </table>			MATERIAL NUMBER	CUSTOMER	SHEET NUMBER	2138651633	OTS	1 OF 1									
INITIAL REVISION:																																						
DRWN: RAVIKM	2021/03/09																																					
APPR: RBBHASKAR	2021/03/17																																					
DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION																																			
2138651633	PSD	000	A																																			
MATERIAL NUMBER	CUSTOMER	SHEET NUMBER																																				
2138651633	OTS	1 OF 1																																				
<table border="1"> <tr> <th>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</th> <th>THIRD ANGLE PROJECTION</th> <th>DRAWING</th> <th>SERIES</th> <th>MATERIAL NUMBER</th> <th>CUSTOMER</th> <th>SHEET NUMBER</th> </tr> <tr> <td></td> <td></td> <td>A3-SIZE</td> <td>213865</td> <td>2138651633</td> <td>OTS</td> <td>1 OF 1</td> </tr> </table>		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER			A3-SIZE	213865	2138651633	OTS	1 OF 1																							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER																																
		A3-SIZE	213865	2138651633	OTS	1 OF 1																																