



THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISS	UE	NUMBER
ORIGINAL		

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED

OPERATING TEMPERATURE: POWER/CO-AX CONTACT RATING: (IF PRESENT)


 $\label{eq:signal_contact_current rating: 5A per contact} SIGNAL CONTACT RESISTANCE: $10 \mbox{m}\Omega$ MAX.$

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: -55°C ~ 125°C ING: 20A (CURRENT) RATING: 5A PER CONTACT E: 10mΩ MAX. 5000MΩ min.

1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-7W2-640-2T1		ISSUE
YOUR CONNECTION			PART NUMBER: 629-7W2-	-640-2T1	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

