



## RJ45-FT

### RJ45 Feed Thru

### IP67 RATED OUTDOOR RJ45 FEED THRU

Laird's RJ45-FT feedthru allows for quick installation of ethernet cables on outdoor equipment or indoor equipment. The feedthru allows for pass thru of the RJ45 connector and sealing of the cable for a weatherproof installation.

### FEATURES

- Pass-thru of RJ45 shielded or unshielded connectors
- Clamps securely to 5 mm min. diameter cables
- Constructed of UV protected materials for long life in harsh outdoor environments.
- Seal meets IP67 criteria.
- Shock and vibration resistant.
- UL and CE rated

### MARKETS

- Wireless base stations
- Wireless client radios
- Direct burial equipment
- Industrial process control
- Telecom equipment
- 802.11 a/b/g wireless Systems
- 10BaseT, 100BaseT or 1000BaseT networks
- Factory automation
- WiMAX

### SPECIFICATIONS

|                        |                                       |
|------------------------|---------------------------------------|
| Material               | UV Resistant Nylon 66 and EPDM rubber |
| Sealing                | IP67                                  |
| Salt Spray             | >1000 h                               |
| Flammability           | UL94VO                                |
| Thermal Shock          | 10 cycles -40 to +100°C               |
| Temperature Range      | -40°C to +85°C                        |
| Installation Hole Dia  | 0.787 in (20 mm)                      |
| Overall Size (L x Dia) | 1.75 x 1 in (44 x 25 mm)              |
| Weight                 | .5 oz (14 gm)                         |

---

## SYSTEM ORDERING INFORMATION

RJ45-FT

RJ45 waterproof outdoor cable feedthru - 10 pack

### NOTES

- All shipments F.O.B. Schaumburg, IL 60173



### TE TECHNICAL SUPPORT CENTER

|                   |                       |
|-------------------|-----------------------|
| USA:              | +1 (800) 522-6752     |
| Canada:           | +1 (905) 475-6222     |
| Mexico:           | +52 (0) 55-1106-0800  |
| Latin/S. America: | +54 (0) 11-4733-2200  |
| Germany:          | +49 (0) 6251-133-1999 |
| UK:               | +44 (0) 800-267666    |
| France:           | +33 (0) 1-3420-8686   |
| Netherlands:      | +31 (0) 73-6246-999   |
| China:            | +86 (0) 400-820-6015  |

### te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original