


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
<DN>	OFF	<DN>
2-3	OPEN	2-1

(<)=Momentary

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT MATERIAL: COPPER ALLOY WITH SILVER PLATE
5. RATING: 2 AMPS @250VAC
5 AMPS @120VAC OR 28VDC
6. OPERATING TEMPERATURE: -30° C TO 85° C
7. ▲ DENOTES CRITICAL PARAMETER.

E-SWITCH®

TITLE					300AWSP4J2WHTM1QE				
SCALE	DATE	DR	DWG	REV	SCALE	DATE	DR	DWG	REV
2:1	9/3/04	AR	T301401	A					

A	14287	RELEASED FOR PRODUCTION	9/3/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED