CHARCTERIST SOURAL shall not be liable for any non-conformity or damage: data data data liable for any non-conformity or damage: data data data data data data data data		т	۵	וד	ш			0	σ		
CHARCTERIST SOURAL shall not be liable for any non-conformity or damage: data data data liable for any non-conformity or damage: data data data data data data data data	4										4
CHARCTERSTCS Standard: Based on MU-DTI-38999 Series II Shell Material ::::::::::::::::::::::::::::::::::::	ω							LAYOUT SHO	VN AS EXAMPLE		3
Standard : Based on MULOTL-38999 Series III Shell Matching ::::::::::::::::::::::::::::::::::::				Keying Shown as	example						
Standard: Based on Mul. DT. 38999 Series II Shell Material: A luminium Shell Material: A luminium Shell Material: A luminium Shell Material: Shell Material: Solid Sectore Countary timeson Solid Sectore Shell Material: Shell Material: Shell Material: Shell Material: Shell Material: Solid Sectore Shell Material: Shell Sectore Shell Sectore Mas: <		CHARACTERISTICS		Г	Connector dimension	7					
Shell MaterNall :: Audminum Shell MaterNall Shell :: Audminum Shell MaterNall Shell :: Audminum Shell :: Audminu		Standard : Based on MIL-DTL-38999 Se	eries III		Dim Nominal						
-Delivered with Souriau contacts and Accessories -Temperature Range :: -65'C to +175'C -Sait Spray :: 28.89 g ± 10% -Mass :: 28.89 g ± 10% BASIC SERIES:: 80 5 17 Z SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact SHELL SIZE : 17 PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: Plug with RFI Shielding CONTACT TYPE :: Plug Store in the property of Subratu Shield Store in the property of Subratu Struct Store Role on the store property of Subratu Shield Store in the property of Subratu Struct Store in the property of Subratu	N	-Shell Plating: Black Zinc Nic-Insulator: Thermoplasti-Contacts: Copper Alloy-Seals & Grommet: Silicon Elasto	ic mer		Z 31 Max			due to a use of the Proo the Specifications issued by	lucts which does not comply either of the Parties or by a th mendation, technical notice. Country Jurisdictior	with hird party) n & Control List	2
-Salt Spray : 500 hours -Mass : 28.89 g ± 10% BASIC SERIES: 8D 5 17 Z 08 P E SHELL SIZE : 17 PLATING : Z = Black Zinc Nickel Contact SHELL SIZE : 17 DATE Latest modification - by MOD N ^a Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Plug 8D series SCALE General linear Tolerance: 859 t. NA CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : Z = Black Zinc Nickel CONTACT TYPE : PlN(500 Matings) CONTACT TYPE : PlN(500 Mati		-Durability : 500 Mating c	ycles				PN: 8D517Z08PE				
-Salt Spray :: 500 hours -Mass :: 28.89 g ± 10% -Mass :: 28.89 g ± 10% BASIC SERIES: 8D 5 - 17 Z 08 P E SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact SHELL SIZE :: 17 PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: PIN(S00 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: PIN(S00 Matings) CONTACT LAYOUT :: 17:08 DESIGNED CONTACT LAYOUT :: 17:08 CONTACT LAYOUT :: 17:08 CONTACT LAYOUT :: 17:08 CONTACT LAYOUT :: 17:08 DESIGNED CONTACT LAYOUT :: 17:08 SHEEL SIZE :: 17 CONTACT LAYOUT :: 17:08 CONTACT LAYOUT :: 17:			5°C				A 18-10-2016	5 First Release			
Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 17 Z 08 P E SHELL TYPE : Plug with RFI Shielding 17 Z 08 P E SCALE General linear Tolerances: 3E39 NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : E NRICH CONTACT TYPE : PIN(500 Matings) This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) FORMAT SOURIAU DRG N° SHEET A3 8D517Z08PE-C 1/2			/) N°
BASIC SERIES: 8D 5 - 17 Z 08 P E Scale NRDS / PROJECT SHELL TYPE : Plug with RFI Shielding - - Scale - Scale NRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : E NA - SOURIAU This document is the property of SOURIAU SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 17-08 FORMAT SOURIAU DRG N° SHEET A3 8D517Z08PE-C 1/2		-ivid55 : 28.89 g ± 10%	0						CU		
BASIC SERIES. ab 3 17 2 08 F 1							TITLE	TITLE Aluminium Plug 8D series			
CONTACT TYPE : Standard Crimp Contact ORIENTATION : E SOURIAU SOURIAU.COM it must not be reproduced or communicated without permission SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings) FORMAT SOURIAU DRG N° SHEET PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-08 FORMAT SOURIAU DRG N° SHEET 1/2 1/2 1/2 1/2 1/2			8D 5 - 17 Z	08 P E				-{	nces:	859	
PLATING : Z = Black Zinc Nickel FORMAT SOURIAU DRG N° SHEET A3 8D517Z08PE-C 1/2			ntact				SOURIAU	WWW.SOURI		SOURIAU it must not be reproduced or	
A3 SOORIAO DIGIN 1/2											
		PLATING : Z = Black Zinc Nickel			CONTACT LA	YOUT : 17-08					
	Ĺ	н	G	F	E			C 8D5	B	1/2	۷

-	Ŧ	۵	п –	m	U	0
		Contact Layout				
4	-х ($ \begin{array}{c} $				
	Conti positio A B C C D E F	Contacts Location X-axis (mm) (mm) + 000 (0.00) + 236 (5.99) + 128 (3.25) + 086 (2.18) + 230 (5.84) - 078 (1.98) + 094 (2.39) - 216 (5.49)				
ယ	G H Shell Arrangement Nu	128 (3.25) +.086 (2.18)				
	-					SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o
N						(professional recommendations issued by entire (professional recommendation) Count FR PN: 8D517
					A 18-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					SOURIAU	
		1	1		FORMAT A3	SOURIAU 8D517Z
	Н	G	l F	E	D	C

