


Material:
 Contact:
 Phosphor Bronze thickness 0.15mm
 Plating:
 Contact Plating, Tin plated 60u"~80u"
 Insulator:
 PBT-4830, UL 94V-0

SPECIFICATIONS:
 Current Rating: 1A
 Dielectric withstanding Voltage: 1000v RMS/minute
 Insulator resistance: 5000 Megohms min.
 Contact resistance: 20 milliohms initial 30 milliohms after test.
 Operating temperatures: -55°C to 85°C
 Insertion force: 340g (12 oz) max. per contact.
 Withdrawal force: 80g (2.82 oz) min. per contact.

Dimensions

Positions	A	B	C	D
① 22	27.94	25.40	12.70	10.16

RoHS compliant
 Unit: mm

Scale	FREE					Date	Name	Customer-No.
TOLERANCE						Drawn	29.07.2014	Amy
X.	±0.38					Approved	17.10.2014	Amy
X.X	±0.25							
X.XX	±0.13							
DIM	TOL	①	Update P/N to 22 pins version	17.10.2014	Ray	 ASSMANN WSW-No. ①A22-LC-T2 Drawing-No. ASS 6528 CO rev01 Replace Sheet		
Angle	±3°	②	Drawn	29.07.2014	Ray			
Angle	TOL	Id.	Modification	Date	Name			