

# NON-INSULATED STRANDED CONDUCTOR, COPPER, TINNED, ROPELAY, 250', 132.52 KCMIL

## CATALOG NUMBER

**LPC127L250**



## CERTIFICATIONS



## FEATURES

Provides a path to ground for lightning currents

## PRODUCT ATTRIBUTES

Certification Details: UL® 96

Material: Copper

Finish: Tinned

UL Conductor Class: Class II

Conductor Type: Ropelay

Number of Wires: 32

Wire Diameter: 0.064"

Diameter: 1/2"

Length: 250'

Cross Section: 132.520 kcmil

Unit Weight: 0.440 lb

## ADDITIONAL PRODUCT DETAILS

---

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

### Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

### Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**