




Data sheet | Item number: 756-5312/030-015

Sensor/Actuator cable; M12A plug; angled; 3-pole; Length: 1.5 m

www.wago.com/756-5312/030-015



i Picture differs from the item.



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	1.5 m
Type code	LiF9YH-11YH or LiF9YC11YFHF

Subject to changes. Please also observe the further product documentation!



Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.1 ... 4.5 mm

Connector

Connection type	M12 plug - free end
Cable connection direction to mating direction	90 °
Connector interface coding (cable/adapter) 1 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	HU
GTIN	4045454942205
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	2bd79c25-0fb1-4da3-8429-8b430928cc66
SCIP notification number (Belgium)	f2e8e667-d230-4c0e-aaa2-fad8cee83882
SCIP notification number (Bulgaria)	6ffc2547-56ef-4654-ae79-71f77236700f
SCIP notification number (Czech Republic)	6a522774-64a0-4b4c-b8bd-c7030df8627d
SCIP notification number (Denmark)	736fd08e-fa9c-4136-97a2-232b5eb34520
SCIP notification number (Finland)	1998c979-5803-4ac2-abbf-8c43442fe7e6

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com


Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



SCIP notification number (France)	1679755b-6a9e-4e5f-9cc2-4d1f95801939
SCIP notification number (Germany)	99b00af0-1a23-489c-a23d-5dc51b9f7bf8
SCIP notification number (Hungary)	e83c6562-53ea-4c1d-8e61-bbc8a2583977
SCIP notification number (Italy)	0889ec03-0a43-42aa-b516-2935aa4c77a0
SCIP notification number (Netherlands)	5d2f6f3a-9c04-41e5-beb7-55e84d6526c7
SCIP notification number (Poland)	ee8f9067-399d-4ad9-8e31-b4bde4552498
SCIP notification number (Romania)	528d7b58-9555-4cee-81ee-611532e32bb3
SCIP notification number (Sweden)	bd488eec-b00d-4499-9f7e-d63ec17db922

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5312/030-015 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5312/030-015 doc - Datei	2017 Sep 20	doc 26.6 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-5312/030-015	URL	Download
WSCAD Universe 756-5312/030-015	URL	Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5312/030-015
Sensor/Actuator cable; M12A plug; angled; 3-pole; Length: 1.5 m

URL

Download

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.