

73605WS Multi-Conductor - 600V Shielded, Light to Moderate Flexing Applications Up to 1 Million Flex Life Cycles



For more Information
please call

1-800-Belden1

General Description:

16 AWG stranded (26x30) bare copper conductors, PVC insulation, oil-resistant PVC inner jacket, tinned copper braid shield, 85% coverage, oil-resistant overall PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------------|-----|-----------|--------------------|-----------|
| 4 | 16 | 26x30 | BC - Bare Copper | 1.524 |

Total Number of Conductors: 5

Ground Wire

Ground Wire (Y/N): Y

Ground Wire AWG: 16

Ground Wire Stranding: 26X30

Ground Wire Conductor Material: BC - Bare Copper

Ground Wire Insulation Material: PVC - Polyvinyl Chloride

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) | Dia. (mm) |
|--------------------------|---------------------|-----------|
| PVC - Polyvinyl Chloride | 0.559 | 2.642 |

Insulation Color Code Chart:

| Color | Description |
|--------------|-----------------------|
| Black | Individually Numbered |
| Yellow/Green | Ground |

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom Wall (mm) | Nom. Dia. (mm) |
|--------------------------|---------------|----------------|
| PVC - Polyvinyl Chloride | 0.762 | 8.915 |

Outer Shield

Outer Shield Material:

| Outer Shield Material | Coverage (%) |
|-----------------------|--------------|
| TC - Tinned Copper | 85.000 |

Outer Shield Separator Material: Tissue Tape, 25#37; Overlap, Min.

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.889 |

Overall Cable

Overall Nominal Diameter: 11.405 mm

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +90°C

Installation Temperature Range: Flexing: -5°C To +90°C

Operating Temperature Range: Flexing: -5°C To +90°C

Bulk Cable Weight: 403.302 Kg/Km

METRIC MEASUREMENT VERSION

73605WS Multi-Conductor - 600V Shielded, Light to Moderate Flexing Applications Up to 1 Million Flex Life Cycles

| | |
|---|------------------|
| Max. Recommended Pulling Tension: | 493.750 N |
| Min. Bend Radius/Minor Axis: | 55.880 mm |
| Min. Bend/Installation: | 55.880 mm |
| Min. Bend Radius (Continuous Flexing): | 55.880 mm |
| Flex Cycle Rating: | 1 Million Flexes |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---|---|
| NEC/(UL) Specification: | THHN/THWN Singles |
| AWM Specification: | UL Style 2587 (600 V 90°C) |
| CSA Specification: | 600 V AWM I/II A/B |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Specification: | AWM/STYLE 2587, AWM I/II A/B, FT1, VDE 0472, Section 803 Oil Test, EU Low Voltage Directive 2014/35/EC, EU Directive 2011/65/EU (RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65 |

Flame Test

| | |
|------------------------|-----|
| CSA Flame Test: | FT1 |
|------------------------|-----|

Electrical Characteristics (Overall)

Nom. Inductance:

| |
|--------------------------|
| Inductance (µH/m) |
| 0.591 |

Nom. Capacitance Cond. to Other Cond. & Ground:

| Description | Freq. (kHz) | Capacitance (pF/m) |
|--------------------|-------------|--------------------|
| Nom. Cond. to Cond | 1.000 | 167.331 |
| Nom. Ground. | 1.000 | 301.852 |

Nom. Conductor DC Resistance:

| |
|----------------------------|
| DCR @ 20°C (Ohm/km) |
| 13.452 |

Nominal Outer Shield DC Resistance:

| |
|----------------------------|
| DCR @ 20°C (Ohm/km) |
| 8.859 |

Put Ups and Colors:

No put ups and colors are available for this product

Revision Number: 0 Revision Date: 09-27-2017

© 2020 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.