



Mushroom pushbutton, 22 mm, round, plastic, yellow, 60 mm, momentary contact type, with laser labeling, inscription or symbol Customer-specific selection with SIRIUS ACT configurator (CIN)

|                                                           |                                                                                                                                 |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>product brand name</b>                                 | SIRIUS ACT                                                                                                                      |
| <b>product designation</b>                                | Mushroom pushbuttons                                                                                                            |
| <b>design of the product</b>                              | Actuating/signaling element                                                                                                     |
| <b>product type designation</b>                           | 3SU1                                                                                                                            |
| <b>product line</b>                                       | Plastic, black, 22 mm                                                                                                           |
| <b>Enclosure</b>                                          |                                                                                                                                 |
| <b>number of command points</b>                           | 1                                                                                                                               |
| <b>Actuator</b>                                           |                                                                                                                                 |
| <b>principle of operation of the actuating element</b>    | momentary contact type                                                                                                          |
| <b>product extension optional light source</b>            | No                                                                                                                              |
| <b>color of the actuating element</b>                     | yellow                                                                                                                          |
| <b>material of the actuating element</b>                  | plastic                                                                                                                         |
| <b>shape of the actuating element</b>                     | round                                                                                                                           |
| <b>outer diameter of the actuating element</b>            | 60 mm                                                                                                                           |
| <b>marking of the actuating element</b>                   | Customized labeling, text or symbols, can only be ordered via SIRIUS ACT configurator/Configuration Identification Number (CIN) |
| <b>number of switching positions</b>                      | 2                                                                                                                               |
| <b>Front ring</b>                                         |                                                                                                                                 |
| <b>product component front ring</b>                       | Yes                                                                                                                             |
| <b>design of the front ring</b>                           | Standard                                                                                                                        |
| <b>material of the front ring</b>                         | plastic                                                                                                                         |
| <b>color of the front ring</b>                            | black                                                                                                                           |
| <b>General technical data</b>                             |                                                                                                                                 |
| <b>product function</b>                                   |                                                                                                                                 |
| • EMERGENCY OFF function                                  | No                                                                                                                              |
| • EMERGENCY STOP function                                 | No                                                                                                                              |
| <b>protection class IP</b>                                | IP66, IP67, IP69(IP69K)                                                                                                         |
| <b>degree of protection NEMA rating</b>                   | 1, 2, 3, 3R, 4, 4X, 12, 13                                                                                                      |
| <b>shock resistance</b>                                   |                                                                                                                                 |
| • according to IEC 60068-2-27                             | sinusoidal half-wave 15g / 11 ms                                                                                                |
| • for railway applications according to EN 61373          | Category 1, Class B                                                                                                             |
| <b>vibration resistance</b>                               |                                                                                                                                 |
| • according to IEC 60068-2-6                              | 10 ... 500 Hz: 5g                                                                                                               |
| • for railway applications according to EN 61373          | Category 1, Class B                                                                                                             |
| <b>operating frequency maximum</b>                        | 3 600 1/h                                                                                                                       |
| <b>mechanical service life (switching cycles) typical</b> | 10 000 000                                                                                                                      |
| <b>reference code according to IEC 81346-2</b>            | S                                                                                                                               |
| <b>Substance Prohibitance (Date)</b>                      | 10/01/2014                                                                                                                      |
| <b>Ambient conditions</b>                                 |                                                                                                                                 |

|                                                                                            |                                                                    |
|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>ambient temperature</b>                                                                 |                                                                    |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul> | <p>-25 ... +70 °C</p> <p>-40 ... +80 °C</p>                        |
| environmental category during operation according to IEC 60721                             | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |

#### Installation/ mounting/ dimensions

|                                                    |         |
|----------------------------------------------------|---------|
| <b>height</b>                                      | 60 mm   |
| <b>width</b>                                       | 60 mm   |
| <b>shape of the installation opening</b>           | round   |
| <b>mounting diameter</b>                           | 22.3 mm |
| <b>positive tolerance of installation diameter</b> | 0.4 mm  |
| <b>mounting height</b>                             | 27.5 mm |
| <b>installation width</b>                          | 60 mm   |
| <b>installation depth</b>                          | 24.4 mm |

#### Certificates/ approvals

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-1CD30-0AA0-Z Y19>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-1CD30-0AA0-Z Y19>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-1CD30-0AA0-Z Y19>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1000-1CD30-0AA0-Z Y19&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-1CD30-0AA0-Z Y19&lang=en)

last modified:

1/27/2022 