

Corded UPS Backplate Outlet Kit for SU6000RT3UHV UPS, 200/208/240V Input/Output, NEMA L6-30R

MODEL NUMBER: SUPDM11



Highlights

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system from hardware in/out to one with an AC plug and outlets
- 10 ft. / 3m AC input cord with NEMA L6-30P plug
- 2 NEMA L6-30R output receptacle
- Easy quick-connect wiring installs in minutes

Description

Tripp Lite's SUPDM11 corded backplate kit converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet. 10 ft./3m input line cord with L6-30P plug enables connection to 200/208/240V 30A mains power. Two L6-30R output receptacles allow for the connection of high current equipment load or power distribution units (PDU). Easy quick-connect wiring installs in minutes.

Features

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Two L6-30R output receptacles pass 200/208/240V output voltage on to connected equipment
- Easy quick-connect wiring installs in minutes

Specifications

| OVERVIEW | |
|-----------------------------|--------------|
| UPC Code | 037332120854 |
| OUTPUT | |
| Output Receptacles | (1) L6-30R |
| Output Nominal Voltage | 200/208/240V |
| INPUT | |
| UPS Input Cord Length (ft.) | 10 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|-------------------------|
| UPS Input Cord Length (m) | 3.1 |
| Recommended Electrical Service | 30A 200/208/240V |
| Input Connection Type | NEMA L6-30P |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 5.50 x 9.00 x 14.25 |
| Shipping Dimensions (hwd / cm) | 13.97 x 22.86 x 36.20 |
| Shipping Weight (lbs.) | 4.62 |
| Shipping Weight (kg) | 2.10 |
| Unit Dimensions (hwd / in.) | 3 x 3.75 x 4.75 |
| Unit Dimensions (hwd / cm) | 7.6 x 9.5 x 12.1 |
| Unit Weight (lbs.) | 4 |
| Unit Weight (kg) | 1.81 |
| Material of Construction | Steel |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>